



COOLANT REPORT

CORROSION	NORMAL
CONTAMINANTS	NORMAL
COOLANT CONDITION	NORMAL

Machine Id
L14-3111 Port Generator (S/N C6T00184)

Component
Coolant
Fluid
CAT EXTENDED LIFE COOLANT (ELC) (125 LTR)

RECOMMENDATION

The fluid is suitable for further service. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0821974	WC0729401	WC0668887
Sample Date		Client Info		04 May 2024	31 Mar 2023	23 Mar 2022
Machine Age	hrs	Client Info		23995	23237	21381
Oil Age	hrs	Client Info		21	1778	0
Oil Changed		Client Info		Not Changd	Not Changd	N/A
Sample Status				NORMAL	NORMAL	NORMAL

CORROSION

All metal levels are normal indicating no corrosion in the cooling system.

Iron	ppm	ASTM D5185(m)	>15	0	1	1
Aluminum	ppm	ASTM D5185(m)	>10	1	7	4
Copper	ppm	ASTM D5185(m)	>10	<1	2	2
Lead	ppm	ASTM D5185(m)	>10	0	0	1
Tin	ppm	ASTM D5185(m)	>10	0	0	0
Silver	ppm	ASTM D5185(m)	>10	<1	0	<1
Zinc	ppm	ASTM D5185(m)	>10	2	3	3

CONTAMINANTS








There is no indication of any contamination in the coolant.

Calcium	ppm	ASTM D5185(m)	>100	4	9	7
Magnesium	ppm	ASTM D5185(m)	>40	1	5	2
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Coolant Appearance		Visual*	Clear	Clear	Clear	Clear

COOLANT CONDITION

The pH level of this fluid is within the acceptable limits. The reserve alkalinity of this fluid is acceptable.

Boiling Point	°C	WC Method*		107	---	---
Specific Gravity		ASTM D1298*	1.070	1.065	1.072	1.072
pH	Scale 0-14	ASTM D1287*	8.3	8.15	7.91	8.01
Nitrites	ppm	Alcan Test Kit*	550	880	680	760
Reserve Alkalinity	Scale 0-20	ASTM D1121*	5.5	3.1	3.0	4.5
Percentage Glycol	%	ASTM D3321*	50	48.0	53.6	53.6
Freezing Point	°C	ASTM D3321*	-37	-35	-43	-43
Carboxylate				---	---	---
Silicon	ppm	ASTM D5185(m)	0	8	33	23
Phosphorus	ppm	ASTM D5185(m)	0	6	2	6
Boron	ppm	ASTM D5185(m)	0	4	4	10
Molybdenum	ppm	ASTM D5185(m)	950	551	678	579
Sodium	ppm	ASTM D5185(m)		5513	3877	2506
Potassium	ppm	ASTM D5185(m)		25	54	62
Coolant Color		Visual*	Red	Orange	Orange	Orange



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0821974 **Received** : 04 Jun 2024
Lab Number : 02639726 **Tested** : 04 Jun 2024
Unique Number : 5788888 **Diagnosed** : 04 Jun 2024 - Kevin Marson
Test Package : COOL (Additional Tests: GlycolType)

CANADIAN COAST GUARD
 CCGS LIMNOS, 867 LAKESHORE ROAD
 BURLINGTON, ON
 CA L7R 4A6
 Contact: Laurie Bosley
 Laurie.Bosley@dfo-mpo.gc.ca
 T:
 F: (519)383-1994

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.