



Machine Id
911023
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (30 LTR)

RECOMMENDATION

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0120697	GFL0107643	GFL0096401
Sample Date		Client Info		04 Jun 2024	12 Mar 2024	27 Sep 2023
Machine Age	kms	Client Info		199234	185680	159846
Oil Age	kms	Client Info		0	0	0
Filter Age	kms	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	Changed
Filter Changed		Client Info		N/A	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>120	11	8	10
Chromium	ppm	ASTM D5185(m)	>20	<1	0	<1
Nickel	ppm	ASTM D5185(m)	>5	0	0	0
Titanium	ppm	ASTM D5185(m)	>2	0	0	0
Silver	ppm	ASTM D5185(m)	>2	0	0	<1
Aluminum	ppm	ASTM D5185(m)	>20	2	2	1
Lead	ppm	ASTM D5185(m)	>40	0	0	<1
Copper	ppm	ASTM D5185(m)	>330	2	1	2
Tin	ppm	ASTM D5185(m)	>15	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0

CONTAMINATION











Il n'y a aucun indice de contamination dans l'huile.

Silicon	ppm	ASTM D5185(m)	>25	4	3	3
Potassium	ppm	ASTM D5185(m)	>20	<1	1	17
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	0.0
Soot %	%	ASTM D7844*	>4	0.6	0.2	0.5
Nitration	Abs/cm	ASTM D7624*	>20	8.4	7.3	8.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	20.4	19.4	19.9
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	NEG

FLUID CONDITION

L'état de l'huile est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		7	4	5
Boron	ppm	ASTM D5185(m)	2	<1	2	2
Barium	ppm	ASTM D5185(m)	0	0	0	<1
Molybdenum	ppm	ASTM D5185(m)	50	60	58	64
Manganese	ppm	ASTM D5185(m)	0	<1	0	0
Magnesium	ppm	ASTM D5185(m)	950	982	958	1016
Calcium	ppm	ASTM D5185(m)	1050	1067	1070	1096
Phosphorus	ppm	ASTM D5185(m)	995	953	971	983
Zinc	ppm	ASTM D5185(m)	1180	1195	1176	1210
Sulfur	ppm	ASTM D5185(m)	2600	2212	2559	2225
Oxidation	Abs/.1mm	ASTM D7414*	>25	15.9	15.0	15.4
Visc @ 100°C	cSt	ASTM D7279(m)	12.00	11.3	11.5	11.4



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : GFL0120697
Lab Number : 02640131
Unique Number : 5789293
Test Package : MOB 1

GFL Environmental - 747 - GMA - Solid Waste
 4 Chemin du Tremblay,
 Boucherville, QC
 CA J4B 6Z5
 Contact: Steve Voyer
 svoyer@matrec.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
F: