

WEAR CONTAMINATION FLUID CONDITION

NORMAL NORMAL

[4593] Machine Id 06-001-CE

Component

| RECOMMENDATION | Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|--|--------------------|------------|-----------------------------|-----------|-------------|----------|----------|
| This is a baseline read-out on the submitted sample. | Sample Number | | Client Info | | PP0001421 | | |
| | Sample Date | | Client Info | | 05 Jun 2024 | | |
| | Machine Age | hrs | Client Info | | 0 | | |
| | Oil Age | hrs | Client Info | | 0 | | |
| | Filter Age | hrs | Client Info | | 0 | | |
| | Oil Changed | | Client Info | | N/A | | |
| | Filter Changed | | Client Info | | N/A | | |
| | Sample Status | | | | NORMAL | | |
| VEAR | Iron | nnm | ACTM DE10E(m) | | | | |
| {not applicable} | Iron | ppm | ASTM D5185(m) | | 0 | | |
| | Chromium | ppm | ASTM D5185(m) | | 0 | | |
| | Nickel | ppm | ASTM D5185(m) | | 0 | | |
| | Titanium | ppm | ASTM D5185(m) | | 0 | | |
| | Silver | ppm | ASTM D5185(m) | | 0 | | |
| | Aluminum | ppm | ASTM D5185(m) | | 0 | | |
| | Lead | ppm | ASTM D5185(m) | | 0 | | |
| | Copper | ppm | ASTM D5185(m) | | 0 | | |
| | Tin | ppm | ASTM D5185(m) | | 0 | | |
| | Vanadium | ppm | ASTM D5185(m) | NONE | 0 | | |
| | White Metal | scalar | Visual* | NONE | NONE | | |
| | Yellow Metal | scalar | Visual* | NONE | NONE | | |
| CONTAMINATION | Silicon | ppm | ASTM D5185(m) | | 0 | | |
| {not applicable} | Potassium | ppm | ASTM D5185(m) | >20 | 0 | | |
| | Water | | WC Method | | NEG | | |
| | Silt | scalar | Visual* | NONE | NONE | | |
| | Debris | scalar | Visual* | NONE | NONE | | |
| | Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| | Appearance | scalar | Visual* | NORML | NORML | | |
| | Odor | scalar | Visual* | NORML | NORML | | |
| LUD CONDITION | 0 " | | AOTM DE (OF () | | | | |
| FLUID CONDITION {not applicable} | Sodium | ppm | ASTM D5185(m) | | 0 | | |
| | Boron | ppm | ASTM D5185(m) | | 0 | | |
| | Barium | ppm | ASTM D5185(m) | | 0 | | |
| | Molybdenum | ppm | ASTM D5185(m) | | 0 | | |
| | Manganese | ppm | ASTM D5185(m) | | 0 | | |
| | Magnesium | ppm | ASTM D5185(m) | | 0 | | |
| | Calcium | ppm | ASTM D5185(m) | | 0 | | |
| | _ | | | | | | |
| | Phosphorus Zinc | ppm ppm | ASTM D5185(m) ASTM D5185(m) | | 0 <1 | | |



CALA ISO 17025:2017 Accredited Laboratory

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Laboratory Sample No. : PP0001421 Lab Number : 02640597

Unique Number : 5789759

To discuss this sample report, contact Customer Service at 1-800-268-2131.

Received **Tested** Diagnosed Test Package : TEST (Additional Tests: ICP, Visual)

: 07 Jun 2024 : 07 Jun 2024

: 07 Jun 2024 - Kevin Marson

CA L2J 1A2 Contact: Mark Michalkoff mmichalkoff@oleoenergies.com T: (905)358-5133

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Oleo Energies

Niagara Falls, ON

5800 Thorold Stone Road