



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
NOVA BUS 170
 Component
Rear Transmission (Auto)
 Fluid
CASTROL TRANSYND (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0866483	WC0888988	WC0889090
Sample Date		Client Info		07 Jun 2024	16 Apr 2024	10 Jan 2024
Machine Age	kms	Client Info		0	0	0
Oil Age	kms	Client Info		36955	28422	19542
Filter Age	kms	Client Info		36955	28422	19542
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>230	30	23	17
Chromium	ppm	ASTM D5185(m)	>2	0	0	0
Nickel	ppm	ASTM D5185(m)	>5	<1	0	<1
Titanium	ppm	ASTM D5185(m)	>2	0	0	0
Silver	ppm	ASTM D5185(m)	>5	<1	0	0
Aluminum	ppm	ASTM D5185(m)	>65	6	5	4
Lead	ppm	ASTM D5185(m)	>55	<1	<1	<1
Copper	ppm	ASTM D5185(m)	>85	4	3	2
Tin	ppm	ASTM D5185(m)	>5	0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
White Metal	scalar	Visual*	NONE	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185(m)	>20	4	3	4
Potassium	ppm	ASTM D5185(m)	>20	<1	<1	1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	Visual*	NONE	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	VLITE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

Sodium	ppm	ASTM D5185(m)		2	2	1
Boron	ppm	ASTM D5185(m)	150	69	72	74
Barium	ppm	ASTM D5185(m)	0	0	0	0
Molybdenum	ppm	ASTM D5185(m)	0	2	<1	2
Manganese	ppm	ASTM D5185(m)		<1	0	0
Magnesium	ppm	ASTM D5185(m)	0	<1	1	<1
Calcium	ppm	ASTM D5185(m)	40	123	126	132
Phosphorus	ppm	ASTM D5185(m)	320	206	213	221
Zinc	ppm	ASTM D5185(m)	5	3	3	4
Sulfur	ppm	ASTM D5185(m)	1050	1363	1348	1574
Acid Number (AN)	mg KOH/g	ASTM D974*	1.0	1.17	0.98	1.02
Visc @ 40°C	cSt	ASTM D7279(m)	38.9	33.1	33.1	33.2
Visc @ 100°C	cSt	ASTM D7279(m)	7.3	6.7	6.7	6.7
Viscosity Index (VI)	Scale	ASTM D2270*	168	164	164	164



ISO 17025:2017
Accredited
Laboratory

Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0866483
Lab Number : 02643771
Unique Number : 5801310
Test Package : MOB 2 (Additional Tests: KV100, TAN Man, VI)

Received : 24 Jun 2024
Tested : 25 Jun 2024
Diagnosed : 25 Jun 2024 - Wes Davis

CITY OF THUNDER BAY
 AUTO MAINTENANCE STORES, 570 FORT WILLIAM ROAD
 THUNDER BAY, ON
 CA P7B 2Z8
 Contact: Sean Malcolm
 sean.malcolm@thunderbay.ca
 T: (807)684-2716
 F: (807)344-0237

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.