WEAR CONTAMINATION **FLUID CONDITION** **NORMAL NORMAL NORMAL**

City of Mount Pearl **FREIGHTLINER 21-20D**

Component
Diesel Engine

SAE 15W40 (--- GAL)

RECOMMENDATION	Test	UOM	Method	Limit/Abn	Current	History1	History2
	Sample Number		Client Info		OF0000838		
Resample at the next service interval to monitor.	Sample Date		Client Info		17 Jun 2024		
	Machine Age	hrs	Client Info		2314		
	Oil Age	hrs	Client Info		1500		
	Filter Age	hrs	Client Info		1500		
	Oil Changed		Client Info		Changed		
	Filter Changed		Client Info		Changed		
	Sample Status				NORMAL		
WEAR	Iron	ppm	ASTM D5185(m)		58		
All common and the same water and the same all	Chromium	ppm	ASTM D5185(m)		2		
All component wear rates are normal.	Nickel	ppm	ASTM D5185(m)		<1		
	Titanium	ppm	ASTM D5185(m)	>2	0		
	Silver	ppm	ASTM D5185(m)	>2	<1		
	Aluminum	ppm	ASTM D5185(m)	>20	11		
	Lead	ppm	ASTM D5185(m)	>40	3		
	Copper	ppm	ASTM D5185(m)	>330	103		
	Tin	ppm	ASTM D5185(m)	>15	<1		
	Vanadium	ppm	ASTM D5185(m)		0		
	White Metal	scalar	Visual*	NONE	VLITE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
CONTAMINATION	Silicon	ppm	ASTM D5185(m)	>25	8		
	Potassium	ppm	ASTM D5185(m)	>20	4		
There is no indication of any contamination in the oil.	Fuel		WC Method	>3.0	<1.0		
	Water		WC Method	>0.2	NEG		
	Glycol		WC Method		NEG		
	Soot %	%	ASTM D7844*	>6	0.6		
	Nitration	Abs/cm	ASTM D7624*	>20	12.0		
	Sulfation	Abs/.1mm	ASTM D7415*	>30	22.0		
	Silt	scalar	Visual*	NONE	VLITE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.2	NEG		
FLUID CONDITION	Sodium	ppm	ASTM D5185(m)	>57	8		
The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.	Boron	ppm	ASTM D5185(m)		1		
	Barium	ppm	ASTM D5185(m)		1		
	Molybdenum	ppm	ASTM D5185(m)		58		
	Manganese	ppm	ASTM D5185(m)		1		
	Magnesium	ppm	ASTM D5185(m)		901		
	Calcium	ppm	ASTM D5185(m)		1025		
	Phosphorus	ppm	ASTM D5185(m)		762		
	Zinc	ppm	ASTM D5185(m)		1137		
	Sulfur	ppm	ASTM D5185(m)		1956		
	Oxidation	Abs/.1mm	ASTM D7414*	>25	18.3		
	Acid Number (AN)	mg KOH/g	ASTM D974*		3.37		
	Base Number (BN)	mg KOH/g	ASTM D2896*		7.88		
	Visc @ 40°C	cSt	ASTM D7279(m)	115	102		
	Visc @ 100°C	cSt	ASTM D7279(m)	14.5	13.8		
	Viscosity Index (VI)	Scale	ASTM D2270*	128	136		





CALA ISO 17025:2017 Accredited

Laboratory

Report Id: FILCON [WCAMIS] 02644118 (Generated: 06/27/2024 10:59:07) Rev: 1

Laboratory Sample No.

: OF0000838 Lab Number : 02644118

To discuss this sample report, contact Customer Service at 1-800-268-2131.

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Unique Number : 5801657

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Received : 26 Jun 2024 **Tested** Diagnosed Test Package : MOB 2 (Additional Tests: KV40, TAN Auto, VI, Visual)

: 27 Jun 2024 : 27 Jun 2024 - Kevin Marson Oil Filtration Solutions Ltd. PO BOX 16125

CONCEPTION BAY SOUTH, NL **CA A1X 2E2**

Contact: BILL BUTLER

BBUTLER@OILFILTRATIONSOLUTIONS.COM T: (709)834-8433

F: (709)834-8435