



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**OR483**  
Component  
**Transmission (Auto)**  
Fluid  
**APRIL SUPERFLO TDH PLUS (--- GAL)**

**RECOMMENDATION**

Échantillonner de nouveau l'équipement au prochain intervalle de vidange afin d'en surveiller la condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0114958</b>	GFL0114957	GFL0089242
Sample Date		Client Info		<b>26 Jun 2024</b>	15 May 2024	05 Apr 2024
Machine Age	hrs	Client Info		<b>12966</b>	12751	12523
Oil Age	hrs	Client Info		<b>0</b>	0	0
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	Not Changd	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

Les taux d'usure de tous les composants sont normaux.

Iron	ppm	ASTM D5185(m)	>160	<b>7</b>	6	6
Chromium	ppm	ASTM D5185(m)	>5	<b>0</b>	0	0
Nickel	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>50	<b>&lt;1</b>	<1	<1
Lead	ppm	ASTM D5185(m)	>50	<b>0</b>	0	0
Copper	ppm	ASTM D5185(m)	>225	<b>3</b>	3	2
Tin	ppm	ASTM D5185(m)	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
White Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**










Il n'y a aucun indice de contamination dans le fluide.

Silicon	ppm	ASTM D5185(m)	>20	<b>3</b>	2	2
Potassium	ppm	ASTM D5185(m)	>20	<b>1</b>	<1	0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	Visual*	NONE	<b>NONE</b>	VLITE	VLITE
Sand/Dirt	scalar	Visual*	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	Visual*	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	Visual*	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

L'état de le fluide est acceptable pour la durée de service.

Sodium	ppm	ASTM D5185(m)		<b>1</b>	1	<1
Boron	ppm	ASTM D5185(m)		<b>4</b>	3	3
Barium	ppm	ASTM D5185(m)		<b>&lt;1</b>	0	0
Molybdenum	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	0
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	0
Magnesium	ppm	ASTM D5185(m)		<b>21</b>	22	21
Calcium	ppm	ASTM D5185(m)		<b>3242</b>	3300	3339
Phosphorus	ppm	ASTM D5185(m)		<b>1201</b>	1240	1251
Zinc	ppm	ASTM D5185(m)		<b>1295</b>	1314	1314
Sulfur	ppm	ASTM D5185(m)		<b>3496</b>	3530	3503
Visc @ 40°C	cSt	ASTM D7279(m)	53.5	<b>41.4</b>	41.9	42.4



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0114958  
**Lab Number** : 02644631  
**Unique Number** : 5802170  
**Test Package** : MOB 1

**GFL Environmental - 784 - Saint-Hyacinthe**  
 3525 Boul. Laurier Est.,  
 Saint-Hyacinthe, QC  
 CA J2R 2B2  
 Contact: Nadine Authier  
 nauthier@matrec.ca  
 T: (450)773-9689  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.