



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**910082**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (35 LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0122321</b>	GFL0117912	GFL0111719
Sample Date		Client Info		<b>28 Jun 2024</b>	11 Apr 2024	06 Mar 2024
Machine Age	hrs	Client Info		<b>9660</b>	9120	8859
Oil Age	hrs	Client Info		<b>600</b>	600	0
Filter Age	hrs	Client Info		<b>600</b>	600	0
Oil Changed		Client Info		<b>Changed</b>	Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185(m)	>120	<b>5</b>	4	8
Chromium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185(m)	>5	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185(m)	>20	<b>1</b>	1	2
Lead	ppm	ASTM D5185(m)	>40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185(m)	>330	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0

**CONTAMINATION**











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185(m)	>25	<b>2</b>	<1	2
Potassium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	<1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	ASTM D7844*	>4	<b>0.3</b>	0.1	0.4
Nitration	Abs/cm	ASTM D7624*	>20	<b>7.4</b>	6.2	8.1
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>19.9</b>	18.7	20.0
Emulsified Water	scalar	Visual*	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185(m)		<b>2</b>	1	1
Boron	ppm	ASTM D5185(m)	0	<b>19</b>	7	10
Barium	ppm	ASTM D5185(m)	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185(m)	60	<b>65</b>	59	61
Manganese	ppm	ASTM D5185(m)	0	<b>&lt;1</b>	0	0
Magnesium	ppm	ASTM D5185(m)	1010	<b>904</b>	957	945
Calcium	ppm	ASTM D5185(m)	1070	<b>1072</b>	1054	1056
Phosphorus	ppm	ASTM D5185(m)	1150	<b>883</b>	987	986
Zinc	ppm	ASTM D5185(m)	1270	<b>1126</b>	1172	1179
Sulfur	ppm	ASTM D5185(m)	2060	<b>2266</b>	2538	2547
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>14.9</b>	13.6	15.2
Visc @ 100°C	cSt	ASTM D7279(m)	15.4	<b>14.2</b>	13.8	13.9



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : GFL0122321  
**Lab Number** : 02645168  
**Unique Number** : 5802707  
**Test Package** : MOB 1

**GFL Environmental - 217 - Aurora**  
 14131 BAYVIEW AVE, AURORA YARD  
 AURORA, ON  
 CA L4G 0K6  
 Contact: Scott Ewan  
 SEwan@gflenv.com  
 T: (647)286-7468  
 F: (905)713-2445

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.