



# OIL ANALYSIS REPORT

WEAR	<b>ABNORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**Store 9 - Marietta**  
Machine Id  
**JOHN DEERE 350G 74345 (S/N 1FF350GXHJF812341)**  
Component  
**Diesel Engine**  
Fluid  
**{not provided} (--- GAL)**

## RECOMMENDATION

We recommend an early resample to monitor this condition.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>LEC0005641</b>	---	---
Sample Date		Client Info		<b>13 Feb 2020</b>	---	---
Machine Age	hrs	Client Info		<b>1754</b>	---	---
Oil Age	hrs	Client Info		<b>0</b>	---	---
Filter Age	hrs	Client Info		<b>0</b>	---	---
Oil Changed		Client Info		<b>N/A</b>	---	---
Filter Changed		Client Info		<b>N/A</b>	---	---
Sample Status				<b>ABNORMAL</b>	---	---

## WEAR

Cylinder, crank, or cam shaft wear is indicated. Bearing wear is indicated. Valve wear is indicated.

Iron	ppm	ASTM D5185m	>51	<b>▲ 85</b>	---	---
Chromium	ppm	ASTM D5185m	>11	<b>2</b>	---	---
Nickel	ppm	ASTM D5185m	>5	<b>▲ 7</b>	---	---
Titanium	ppm	ASTM D5185m		<b>4</b>	---	---
Silver	ppm	ASTM D5185m		<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m	>31	<b>4</b>	---	---
Lead	ppm	ASTM D5185m	>26	<b>2</b>	---	---
Copper	ppm	ASTM D5185m	>26	<b>▲ 143</b>	---	---
Tin	ppm	ASTM D5185m	>4	<b>2</b>	---	---
Vanadium	ppm	ASTM D5185m		<b>0</b>	---	---
White Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	---	---

## CONTAMINATION

There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	<b>5</b>	---	---
Potassium	ppm	ASTM D5185m	>20	<b>7</b>	---	---
Fuel		WC Method	>2.1	<b>&lt;1.0</b>	---	---
Water	%	ASTM D6304	>0.21	<b>0.112</b>	---	---
ppm Water	ppm	ASTM D6304	>2100	<b>1120</b>	---	---
Glycol	%	*ASTM D2982		<b>NEG</b>	---	---
Soot %	%	*ASTM D7844	>3	<b>0.5</b>	---	---
Nitration	Abs/cm	*ASTM D7624	>20	<b>10</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>25.3</b>	---	---
Silt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Debris	scalar	*Visual	NONE	<b>NONE</b>	---	---
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	---	---
Appearance	scalar	*Visual	NORML	<b>NORML</b>	---	---
Odor	scalar	*Visual	NORML	<b>NORML</b>	---	---
Emulsified Water	scalar	*Visual	>0.21	<b>NEG</b>	---	---

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>31	<b>10</b>	---	---
Boron	ppm	ASTM D5185m		<b>12</b>	---	---
Barium	ppm	ASTM D5185m		<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185m		<b>31</b>	---	---
Manganese	ppm	ASTM D5185m		<b>2</b>	---	---
Magnesium	ppm	ASTM D5185m		<b>651</b>	---	---
Calcium	ppm	ASTM D5185m		<b>1486</b>	---	---
Phosphorus	ppm	ASTM D5185m		<b>978</b>	---	---
Zinc	ppm	ASTM D5185m		<b>1080</b>	---	---
Sulfur	ppm	ASTM D5185m		<b>2461</b>	---	---
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>16.8</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896		<b>6.8</b>	---	---
Visc @ 100°C	cSt	ASTM D445		<b>12.5</b>	---	---



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : LEC0005641 **Received** : 27 Feb 2020  
**Lab Number** : 04921727 **Diagnosed** : 28 Feb 2020  
**Unique Number** : 8941819 **Diagnostician** : Don Baldrige  
**Test Package** : MOBCE ( Additional Tests: Glycol, KF, PQ, TBN )

**BRIDGEPORT EQUIPMENT & TOOL**  
 15 ACME ST  
 MARIETTA, OH  
 US 45750  
 Contact: FRED ELLIS  
 fellis@bridgeportequip.com  
 T:  
 F: (740)373-3895

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)