



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
413024

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0064657	GFL0046855	GFL0046828
Sample Date		Client Info		13 Jan 2023	08 Dec 2022	08 Nov 2022
Machine Age	hrs	Client Info		842	659	491
Oil Age	hrs	Client Info		183	659	491
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Not Changd
Filter Changed		Client Info		Changed	Changed	Not Changd
Sample Status				NORMAL	ABNORMAL	ABNORMAL

WEAR

Metal levels are typical for a new component breaking in.

Iron	ppm	ASTM D5185m	>100	9	39	31
Chromium	ppm	ASTM D5185m	>20	<1	2	1
Nickel	ppm	ASTM D5185m	>4	0	7	4
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	<1	<1	1
Aluminum	ppm	ASTM D5185m	>20	3	▲ 18	15
Lead	ppm	ASTM D5185m	>40	<1	5	<1
Copper	ppm	ASTM D5185m	>330	99	263	227
Tin	ppm	ASTM D5185m	>15	<1	5	4
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	10	▲ 79	▲ 78
Potassium	ppm	ASTM D5185m	>20	11	47	37
Fuel		WC Method	>5	<1.0	<1.0	0.6
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.3	0.2
Nitration	Abs/cm	*ASTM D7624	>20	6.4	11.4	10.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.8	26.1	25.6
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		0	4	3
Boron	ppm	ASTM D5185m	0	13	161	237
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	62	117	116
Manganese	ppm	ASTM D5185m	0	<1	4	4
Magnesium	ppm	ASTM D5185m	1010	828	759	698
Calcium	ppm	ASTM D5185m	1070	1049	1494	1424
Phosphorus	ppm	ASTM D5185m	1150	940	762	654
Zinc	ppm	ASTM D5185m	1270	1081	876	791
Sulfur	ppm	ASTM D5185m	2060	2511	2412	2622
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.7	25.1	23.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.4	8.1	8.9
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	▲ 10.1	▲ 9.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0064657 **Received** : 17 Jan 2023
Lab Number : 05741300 **Diagnosed** : 18 Jan 2023
Unique Number : 10295899 **Diagnostician** : Wes Davis
Test Package : FLEET

GFL Environmental - 814 - Little Rock Hauling
 4005 Hwy 161 N.
 Little Rock, AR
 US 72117
 Contact: Brad Koenig
 bkoenig@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)