



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
Store 4 - Fairmont
Machine Id
JOHN DEERE 624L 1DW624LZTKF694098
Component
Front Axle
Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0038873	LEC0028615	LEC0028043
Sample Date		Client Info		09 Feb 2023	09 May 2022	02 Feb 2022
Machine Age	hrs	Client Info		3998	3354	2972
Oil Age	hrs	Client Info		1505	861	479
Filter Age	hrs	Client Info		0	861	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		None	Changed	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		31	17	40
Iron	ppm	ASTM D5185m	>750	99	11	79
Chromium	ppm	ASTM D5185m	>11	<1	0	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	<1
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>21	1	1	2
Lead	ppm	ASTM D5185m	>49	3	<1	4
Copper	ppm	ASTM D5185m	>101	9	<1	6
Tin	ppm	ASTM D5185m	>10	1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	VLITE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>31	11	5	9
Potassium	ppm	ASTM D5185m	>20	<1	0	1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	VLITE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	3	<1	2
Boron	ppm	ASTM D5185m	6	2	6	4
Barium	ppm	ASTM D5185m	0	<1	0	0
Molybdenum	ppm	ASTM D5185m	0	3	4	2
Manganese	ppm	ASTM D5185m		2	<1	2
Magnesium	ppm	ASTM D5185m	145	101	117	114
Calcium	ppm	ASTM D5185m	3570	3307	3508	3746
Phosphorus	ppm	ASTM D5185m	1290	940	1021	1098
Zinc	ppm	ASTM D5185m	1640	1180	1221	1261
Sulfur	ppm	ASTM D5185m		3886	3168	3306
Visc @ 40°C	cSt	ASTM D445	57.0	55.5	58.6	54.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0038873 **Received** : 15 Feb 2023
Lab Number : 05768305 **Tested** : 16 Feb 2023
Unique Number : 10337913 **Diagnosed** : 16 Feb 2023 - Sean Felton
Test Package : CONST (Additional Tests: PQ)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (740)373-5570