



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
VOLVO VNL UNIT 13 (S/N 176765A)

Component
Diesel Engine

Fluid
LUCAS SYN BLEND 10W30 (38 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LF1501606	LF1501598	LF509802
Sample Date		Client Info		28 Feb 2023	01 Feb 2023	18 May 2022
Machine Age	mls	Client Info		0	905596	863491
Oil Age	mls	Client Info		8545	35470	16224
Filter Age	mls	Client Info		8545	35470	16224
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	14	43	19
Chromium	ppm	ASTM D5185m	>20	<1	1	<1
Nickel	ppm	ASTM D5185m	>2	0	2	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	8	19	12
Lead	ppm	ASTM D5185m	>40	<1	5	<1
Copper	ppm	ASTM D5185m	>330	2	4	2
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	9	10
Potassium	ppm	ASTM D5185m	>20	<1	2	2
Fuel		WC Method	>5	<1.0	1.8	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.4	1.2	0.7
Nitration	Abs/cm	*ASTM D7624	>20	7.4	10.3	8.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.0	26.6	23.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	5	0
Boron	ppm	ASTM D5185m		263	35	226
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		122	115	121
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		543	515	565
Calcium	ppm	ASTM D5185m		1385	1335	1446
Phosphorus	ppm	ASTM D5185m		836	758	931
Zinc	ppm	ASTM D5185m		1062	1002	1168
Sulfur	ppm	ASTM D5185m		3379	2894	2535
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.5	21.3	19.4
Base Number (BN)	mg KOH/g	ASTM D2896		8.8	5.5	7.6
Visc @ 100°C	cSt	ASTM D445		11.2	10.7	11.0



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LF1501606 **Received** : 10 Mar 2023
Lab Number : 05789043 **Tested** : 13 Mar 2023
Unique Number : 10373714 **Diagnosed** : 13 Mar 2023 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

WILLIS TRUCKING
 1793 COUNTY RD 25
 BROSELEY, MO
 US 63932

Contact: SCOTT
 accounting@willistruckingllc.com
 T: (573)472-2650
 F: (573)472-2651

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)