



| | |
|-----------------|---------------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |

Machine Id
JOHN DEERE 35G 1FF035GXPJK282679

Component
Hydraulic System

Fluid
JOHN DEERE HYDRAU (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|--------------------|----------|----------|
| Sample Number | | Client Info | | JR0162041 | --- | --- |
| Sample Date | | Client Info | | 17 May 2023 | --- | --- |
| Machine Age | hrs | Client Info | | 661 | --- | --- |
| Oil Age | hrs | Client Info | | 661 | --- | --- |
| Filter Age | hrs | Client Info | | 661 | --- | --- |
| Oil Changed | | Client Info | | Not Changed | --- | --- |
| Filter Changed | | Client Info | | Changed | --- | --- |
| Sample Status | | | | NORMAL | --- | --- |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|------|--------------|-----|-----|
| PQ | | ASTM D8184 | >50 | 17 | --- | --- |
| Iron | ppm | ASTM D5185m | >32 | 4 | --- | --- |
| Chromium | ppm | ASTM D5185m | >9 | 0 | --- | --- |
| Nickel | ppm | ASTM D5185m | >5 | <1 | --- | --- |
| Titanium | ppm | ASTM D5185m | | 0 | --- | --- |
| Silver | ppm | ASTM D5185m | | 0 | --- | --- |
| Aluminum | ppm | ASTM D5185m | >9 | 0 | --- | --- |
| Lead | ppm | ASTM D5185m | >28 | 0 | --- | --- |
| Copper | ppm | ASTM D5185m | >50 | <1 | --- | --- |
| Tin | ppm | ASTM D5185m | >5 | <1 | --- | --- |
| Vanadium | ppm | ASTM D5185m | | 0 | --- | --- |
| White Metal | scalar | *Visual | NONE | NONE | --- | --- |
| Yellow Metal | scalar | *Visual | NONE | NONE | --- | --- |

CONTAMINATION











The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|--------------|-----------|-----------------|-----|-----|
| Silicon | ppm | ASTM D5185m | >11 | <1 | --- | --- |
| Potassium | ppm | ASTM D5185m | >20 | 2 | --- | --- |
| Water | | WC Method | >0.075 | NEG | --- | --- |
| Particles >4µm | | ASTM D7647 | >80000 | 17617 | --- | --- |
| Particles >6µm | | ASTM D7647 | >20000 | 2266 | --- | --- |
| Particles >14µm | | ASTM D7647 | >640 | 22 | --- | --- |
| Particles >21µm | | ASTM D7647 | >160 | 3 | --- | --- |
| Particles >38µm | | ASTM D7647 | >40 | 0 | --- | --- |
| Particles >71µm | | ASTM D7647 | >10 | 0 | --- | --- |
| Oil Cleanliness | | ISO 4406 (c) | >23/21/16 | 21/18/12 | --- | --- |
| Silt | scalar | *Visual | NONE | NONE | --- | --- |
| Debris | scalar | *Visual | NONE | NONE | --- | --- |
| Sand/Dirt | scalar | *Visual | NONE | NONE | --- | --- |
| Appearance | scalar | *Visual | NORML | NORML | --- | --- |
| Odor | scalar | *Visual | NORML | NORML | --- | --- |
| Emulsified Water | scalar | *Visual | >0.075 | NEG | --- | --- |

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | | | | | | |
|------------------|----------|-------------|------|--------------|-----|-----|
| Sodium | ppm | ASTM D5185m | >21 | <1 | --- | --- |
| Boron | ppm | ASTM D5185m | | 0 | --- | --- |
| Barium | ppm | ASTM D5185m | | 0 | --- | --- |
| Molybdenum | ppm | ASTM D5185m | | 0 | --- | --- |
| Manganese | ppm | ASTM D5185m | | <1 | --- | --- |
| Magnesium | ppm | ASTM D5185m | | 4 | --- | --- |
| Calcium | ppm | ASTM D5185m | 87 | 6 | --- | --- |
| Phosphorus | ppm | ASTM D5185m | 727 | 325 | --- | --- |
| Zinc | ppm | ASTM D5185m | 900 | 79 | --- | --- |
| Sulfur | ppm | ASTM D5185m | 1500 | 1528 | --- | --- |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 1.0 | 0.11 | --- | --- |
| Visc @ 40°C | cSt | ASTM D445 | 65 | 45.9 | --- | --- |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0162041 **Received** : 23 May 2023
Lab Number : 05855003 **Tested** : 25 May 2023
Unique Number : 10484358 **Diagnosed** : 25 May 2023 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

JRE - STATESVILLE
 635 MOCKSVILLE HWY
 STATESVILLE, NC
 US 28625

Contact: MIKE CRANFILL
 MCRANFILL@JAMESRIVEREQUIPMENT.COM

T: (704)872-6411

F: