



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
Capt Greg Smith (S/N 71-C1-1056)
Component
Port Main Engine
Fluid
CHEVRON DELO 710 LS (350 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0056136	MW0056117	MW0037546
Sample Date		Client Info		14 Aug 2023	27 Jun 2023	15 May 2023
Machine Age	hrs	Client Info		15308	14207	13248
Oil Age	hrs	Client Info		2539	1239	277
Filter Age	hrs	Client Info		950	1239	277
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Filter Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	10	8	5
Chromium	ppm	ASTM D5185m	>8	1	1	0
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	2	<1	<1
Lead	ppm	ASTM D5185m	>18	8	5	▲ 15
Copper	ppm	ASTM D5185m	>80	15	14	12
Tin	ppm	ASTM D5185m	>14	4	4	2
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	3	3	3
Potassium	ppm	ASTM D5185m	>20	36	79	126
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.5	0.2
Nitration	Abs/cm	*ASTM D7624	>20	8.7	8.6	8.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	16.6	16.6	14.2
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	7	13	24
Boron	ppm	ASTM D5185m		39	42	40
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		51	56	57
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		16	14	11
Calcium	ppm	ASTM D5185m		3496	3653	3383
Phosphorus	ppm	ASTM D5185m		5	10	2
Zinc	ppm	ASTM D5185m		6	0	0
Sulfur	ppm	ASTM D5185m		2552	2816	2606
Oxidation	Abs/.1mm	*ASTM D7414	>25	8.9	9.0	7.0
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	7.1	7.2	8.3
Visc @ 100°C	cSt	ASTM D445	15.5	14.7	14.8	14.6



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0056136
Lab Number : 05931895
Unique Number : 10617166
Test Package : MAR 2

Received : 23 Aug 2023
Tested : 24 Aug 2023
Diagnosed : 24 Aug 2023 - Wes Davis

AMERICAN COMMERCIAL LINES
 PO BOX 610, 1701 E. MARKET STREET
 JEFFERSONVILLE, IN
 US 47130
 Contact: RONALD SCHNEIDER
 ronald.schneider@bargeacbl.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (812)288-1644