



TRAAP

Texas Refinery Advanced Analysis Program

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 2955 JD 2955
 Component
Diesel Engine
 Fluid
TRC MOLY XL PRO-SPEC IV XP 15W40 (3 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TR05957165	TR05887549	TR05824509
Sample Date		Client Info		13 Sep 2023	23 Jun 2023	08 Apr 2023
Machine Age	hrs	Client Info		17930	17800	17675
Oil Age	hrs	Client Info		600	450	345
Filter Age	hrs	Client Info		600	450	345
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	61	48	46
Chromium	ppm	ASTM D5185m	>11	1	1	<1
Nickel	ppm	ASTM D5185m	>5	1	1	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	<1	4	1
Lead	ppm	ASTM D5185m	>26	2	<1	0
Copper	ppm	ASTM D5185m	>26	2	3	3
Tin	ppm	ASTM D5185m	>4	1	<1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	8	7	9
Potassium	ppm	ASTM D5185m	>20	4	3	0
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	14.0	13.1	12.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	25.1	24.3	20.8
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	3	3	3
Boron	ppm	ASTM D5185m		8	12	10
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		132	124	119
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		25	23	21
Calcium	ppm	ASTM D5185m		4691	4569	4030
Phosphorus	ppm	ASTM D5185m		981	968	894
Zinc	ppm	ASTM D5185m		1204	1192	1078
Sulfur	ppm	ASTM D5185m		5031	5345	4425
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.9	18.8	15.7
Base Number (BN)	mg KOH/g	ASTM D2896		12.57	13.19	13.94
Visc @ 100°C	cSt	ASTM D445		15.2	15.0	14.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TR05957165
Lab Number : 05957165
Unique Number : 10658378
Test Package : MOB 2
Received : 20 Sep 2023
Tested : 26 Sep 2023
Diagnosed : 27 Sep 2023 - Jonathan Hester

SPRAGUE RANCH
 6907 ROUTE 14
 BROOKFIELD, VT
 US 05036
 Contact: SCOTT BURRELL

To discuss this sample report, contact Customer Service at 1-800-827-0711.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: