



Built for a lifetime™

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
KAESER 7252705
 Component
Compressor
 Fluid
KAESER SIGMA (OEM) M-460 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		KCPA007806	KCPA004462	KCP52292
Sample Date		Client Info		04 Oct 2023	21 Jul 2023	18 May 2023
Machine Age	hrs	Client Info		8102	7278	6393
Oil Age	hrs	Client Info		0	0	2100
Filter Age	hrs	Client Info		0	0	2100
Oil Changed		Client Info		N/A	N/A	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ATTENTION	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>10	0	<1	<1
Copper	ppm	ASTM D5185m	>50	<1	1	3
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	MODER

CONTAMINATION











There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Silicon	ppm	ASTM D5185m	>25	<1	0	2
Potassium	ppm	ASTM D5185m	>20	2	4	4
Water	%	ASTM D6304	>0.05	0.015	0.037	0.017
ppm Water	ppm	ASTM D6304	>500	155.6	372.1	177.8
Particles >4µm		ASTM D7647		2366	5518	---
Particles >6µm		ASTM D7647	>1300	600	▲ 1609	---
Particles >14µm		ASTM D7647	>80	70	▲ 95	---
Particles >21µm		ASTM D7647	>20	23	▲ 21	---
Particles >38µm		ASTM D7647	>4	1	0	---
Particles >71µm		ASTM D7647	>3	0	0	---
Oil Cleanliness		ISO 4406 (c)	---/17/13	18/16/13	▲ 20/18/14	---
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	▲ LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		9	5	13
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	49	57	69
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	78	78	80
Calcium	ppm	ASTM D5185m	0	0	0	2
Phosphorus	ppm	ASTM D5185m	0	3	0	1
Zinc	ppm	ASTM D5185m	0	0	2	4
Sulfur	ppm	ASTM D5185m	23500	19386	21859	21339
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.42	0.42	0.43
Visc @ 40°C	cSt	ASTM D445	45	48.0	47.9	48.8



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KCPA007806 **Received** : 18 Oct 2023
Lab Number : 05982375 **Diagnosed** : 20 Oct 2023
Unique Number : 10699670 **Diagnostician** : Angela Borella
Test Package : IND 2 (Additional Tests: KF, PrtCount)

AMAZON.COM SERVICES
 4222 INTERGRATIONS LOOP
 COLORADO SPRINGS, CO
 US 80916
 Contact: Service Manager

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: