



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[16W14764]
 Machine Id
JOHN DEERE 210G 1FF210GXEMF529192
 Component
Diesel Engine
 Fluid
JOHN DEERE ENGINE OIL PLUS 50 II 15W40 (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor. (Customer Sample Comment: 16W14764)

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0185406	JR0153647	JR0121838
Sample Date		Client Info		19 Oct 2023	06 Dec 2022	01 Apr 2022
Machine Age	hrs	Client Info		2538	2061	1058
Oil Age	hrs	Client Info		477	1003	622
Filter Age	hrs	Client Info		477	1003	622
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>51	22	40	32
Chromium	ppm	ASTM D5185m	>11	<1	1	1
Nickel	ppm	ASTM D5185m	>5	4	3	▲ 10
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>31	6	4	4
Lead	ppm	ASTM D5185m	>26	<1	3	1
Copper	ppm	ASTM D5185m	>26	6	14	▲ 70
Tin	ppm	ASTM D5185m	>4	<1	0	2
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>22	7	8	7
Potassium	ppm	ASTM D5185m	>20	4	0	2
Fuel		WC Method	>2.1	<1.0	<1.0	<1.0
Water		WC Method	>0.21	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.7	1.5	1
Nitration	Abs/cm	*ASTM D7624	>20	9.4	12.8	11.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.4	31.3	27.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.21	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>31	1	0	4
Boron	ppm	ASTM D5185m		127	42	116
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		223	189	201
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		683	620	767
Calcium	ppm	ASTM D5185m		1651	1979	1855
Phosphorus	ppm	ASTM D5185m		933	946	940
Zinc	ppm	ASTM D5185m		1176	1204	1141
Sulfur	ppm	ASTM D5185m		3431	3585	2604
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.1	25.2	23.0
Base Number (BN)	mg KOH/g	ASTM D2896	13.6	7.3	7.9	8.7
Visc @ 100°C	cSt	ASTM D445	15.4	14.3	14.6	14.02



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0185406 **Received** : 23 Oct 2023
Lab Number : 05986343 **Tested** : 24 Oct 2023
Unique Number : 10709005 **Diagnosed** : 25 Oct 2023 - Don Baldrige
Test Package : CONST (Additional Tests: TBN)

JRE - CASTLE HAYNE
 113 CROWATAN ROAD
 CASTLE HAYNE, NC
 US 28429-5819

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: WILMINGTON SHOP
 todd.simmons@jamesriverequipment.com; canastasio@wearcheck.com; canastasio@we

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (910)675-9211 F:

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)