



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id **CATERPILLAR 775D 6441 (S/N 8AS00350)**

Component **Hydraulic System**

Fluid **TULCO LUBSOIL SUPER HYDRAULIC HZ 46 (--- GAL)**

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TO10002871	TO10002446	TO10002303
Sample Date		Client Info		13 Nov 2023	09 Aug 2023	26 May 2023
Machine Age	hrs	Client Info		42811	42272	41797
Oil Age	hrs	Client Info		4058	3519	3044
Filter Age	hrs	Client Info		539	475	495
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Changd	Changd	Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>20	3	3	3
Chromium	ppm	ASTM D5185m	>20	<1	0	0
Nickel	ppm	ASTM D5185m	>20	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	1	1	<1
Tin	ppm	ASTM D5185m	>20	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Silicon	ppm	ASTM D5185m	>15	3	4	4
Potassium	ppm	ASTM D5185m	>20	0	0	<1
Water	%	ASTM D6304	>0.05	NEG	NEG	NEG
Particles >4µm		ASTM D7647	>5000	3291	1955	2948
Particles >6µm		ASTM D7647	>1300	396	244	381
Particles >14µm		ASTM D7647	>160	10	15	14
Particles >21µm		ASTM D7647	>40	1	6	4
Particles >38µm		ASTM D7647	>10	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	19/16/10	18/15/11	19/16/11
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	2	1
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		114	160	154
Calcium	ppm	ASTM D5185m		111	146	146
Phosphorus	ppm	ASTM D5185m		669	753	823
Zinc	ppm	ASTM D5185m		893	940	1069
Sulfur	ppm	ASTM D5185m		2479	3395	3809
Acid Number (AN)	mg KOH/g	ASTM D8045		0.68	0.97	1.05
Visc @ 40°C	cSt	ASTM D445		47.6	47.2	47.3
Visc @ 100°C	cSt	ASTM D445		7.13	7.1	7
Viscosity Index (VI)	Scale	ASTM D2270		108	108	104



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TO10002871
Lab Number : 06011486
Unique Number : 10750630
Test Package : MOB 2 (Additional Tests: KF, KV100, VI)
Received : 17 Nov 2023
Tested : 29 Nov 2023
Diagnosed : 29 Nov 2023 - Jonathan Hester

ANCHOR STONE TULSA ROCK
 TULSA ROCK QUARRY, 66TH ST N 145TH AVENUE
 TULSA, OK
 US 74137
 Contact: MIKE SNYDER
 msnyder@anchorstoneco.com
 T: (417)850-9635
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)