



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 724K 1DW724KHJJF690939
Component
Front Differential
Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0195230	JR0195221	JR0184986
Sample Date		Client Info		15 Nov 2023	15 Nov 2023	12 Sep 2023
Machine Age	hrs	Client Info		5118	5118	4907
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	Not Changd	Not Changd
Sample Status				NORMAL	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

PQ	UOM	Method	Limit/Abn	Current	History1	History2
PQ		ASTM D8184		12	8	20
Iron	ppm	ASTM D5185m	>500	55	9	52
Chromium	ppm	ASTM D5185m	>10	<1	3	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>25	1	1	5
Lead	ppm	ASTM D5185m	>25	66	0	60
Copper	ppm	ASTM D5185m	>100	19	2	18
Tin	ppm	ASTM D5185m	>10	1	0	1
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Silicon	ppm	ASTM D5185m	>75	5	2	5
Potassium	ppm	ASTM D5185m	>20	<1	2	1
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sodium	ppm	ASTM D5185m		4	0	4
Boron	ppm	ASTM D5185m	6	12	0	13
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	24	<1	21
Manganese	ppm	ASTM D5185m		1	0	1
Magnesium	ppm	ASTM D5185m	145	125	2	127
Calcium	ppm	ASTM D5185m	3570	2887	99	3055
Phosphorus	ppm	ASTM D5185m	1290	971	596	973
Zinc	ppm	ASTM D5185m	1640	1123	797	1139
Sulfur	ppm	ASTM D5185m		3241	1820	3960
Visc @ 40°C	cSt	ASTM D445	57.0	52.9	57.6	52.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0195230 **Received** : 22 Nov 2023
Lab Number : 06015337 **Tested** : 24 Nov 2023
Unique Number : 10754481 **Diagnosed** : 26 Nov 2023 - Don Baldrige
Test Package : CONST (Additional Tests: PQ)

W&L CONSTRUCTION AND PAVING
 DRAWER 927
 CHILHOWIE, VA
 US 24319
 Contact: TRAVIS LEWIS

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (276)646-3804

F: