



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[3]
 Machine Id
VOLVO L70F 62487
 Component
Diesel Engine
 Fluid
MOBIL DELVAC 1300 SUPER15W40 (--- GAL)

RECOMMENDATION

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP430543	VCP324026	VCP351312
Sample Date		Client Info		14 Dec 2023	12 Apr 2023	23 Jun 2022
Machine Age	hrs	Client Info		28409	26979	26689
Oil Age	hrs	Client Info		500	400	600
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	5	4	9
Chromium	ppm	ASTM D5185m	>10	<1	<1	<1
Nickel	ppm	ASTM D5185m	>10	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>10	1	<1	2
Lead	ppm	ASTM D5185m	>20	<1	<1	<1
Copper	ppm	ASTM D5185m	>15	<1	0	1
Tin	ppm	ASTM D5185m	>10	<1	1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	2	8	4
Potassium	ppm	ASTM D5185m	>20	<1	2	2
Fuel	%	ASTM D3524	>6.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.1	0.3
Nitration	Abs/cm	*ASTM D7624	>20	6.2	7.6	8.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.2	15.4	18.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	2	4
Boron	ppm	ASTM D5185m	0	5	63	11
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	61	83	52
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	0	952	109	790
Calcium	ppm	ASTM D5185m		1045	2101	1268
Phosphorus	ppm	ASTM D5185m		1059	1075	1020
Zinc	ppm	ASTM D5185m		1273	1286	1237
Sulfur	ppm	ASTM D5185m		3366	4649	3812
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.5	12.1	14.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	9.4	6.3	8.0
Visc @ 100°C	cSt	ASTM D445	14	12.4	13.3	12.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP430543 **Received** : 02 Jan 2024
Lab Number : 06048665 **Diagnosed** : 08 Jan 2024
Unique Number : 10809273 **Diagnostician** : Doug Bogart
Test Package : MOB 1 (Additional Tests: FUELDILUTION, PercentFuel, TBN)

PLEASANT RIVER LUMBER
 PO BOX 68
 DOVER FOXCROFT, ME
 US 04426
 Contact: BURLEY HIGGINS
 burley@pleasantriverlumber.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
 F: (207)564-8259