



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
BURKEVILLE
Machine Id
JOHN DEERE 300D M01-0306 1DW300DXACE645790
Component
Rear Right Final Drive
Fluid
JOHN DEERE GL-5 80W90 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0180634	JRMC412785	LECP160126
Sample Date		Client Info		28 Dec 2023	25 Mar 2016	11 Aug 2015
Machine Age	hrs	Client Info		12383	2723	2456
Oil Age	hrs	Client Info		0	0	473
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	54	28.0	44.0
Iron	ppm	ASTM D5185m	>750	55	270	242
Chromium	ppm	ASTM D5185m	>9	0	2	1
Nickel	ppm	ASTM D5185m	>10	0	<1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>40	0	4	3
Lead	ppm	ASTM D5185m	>15	0	0	0
Copper	ppm	ASTM D5185m	>40	6	7	6
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	LIGHT	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the component.

Silicon	ppm	ASTM D5185m	>75	3	2	1
Potassium	ppm	ASTM D5185m	>20	0	<1	<1
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<1	2	1
Boron	ppm	ASTM D5185m		6	3	2
Barium	ppm	ASTM D5185m		0	<1	0
Molybdenum	ppm	ASTM D5185m		<1	7	6
Manganese	ppm	ASTM D5185m		<1	5	4
Magnesium	ppm	ASTM D5185m		0	<1	0
Calcium	ppm	ASTM D5185m		0	16	2
Phosphorus	ppm	ASTM D5185m		557	773	738
Zinc	ppm	ASTM D5185m		0	15	7
Sulfur	ppm	ASTM D5185m		27988	22589	27909
Visc @ 40°C	cSt	ASTM D445		130	141.4	142.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0180634 **Received** : 02 Jan 2024
Lab Number : 06049199 **Diagnosed** : 05 Jan 2024
Unique Number : 10809807 **Diagnostician** : Angela Borella
Test Package : CONST (Additional Tests: PQ)

LUCK STONE
 19380 RICHMOND TURNPIKE
 MILFORD, VA
 US 22514
 Contact: BRYAN MORRIS
 bmorris@luckstone.com
 T: (804)400-3630
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)