



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Area  
**MARTHA LYNN**  
Machine Id  
**[MARTHA LYNN] 002 504678-2**  
Component  
**Center Main Engine**  
Fluid  
**CHEVRON DELO 710 LS (350 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0061349</b>	MW0058750	MW0053536
Sample Date		Client Info		<b>01 Nov 2023</b>	01 Sep 2023	01 Aug 2023
Machine Age	hrs	Client Info		<b>16633</b>	15608	15016
Oil Age	hrs	Client Info		<b>16633</b>	15608	15016
Filter Age	hrs	Client Info		<b>16633</b>	15608	630
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>None</b>	None	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	<b>10</b>	11	10
Chromium	ppm	ASTM D5185m	>8	<b>&lt;1</b>	1	1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>3	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>15	<b>1</b>	3	<1
Lead	ppm	ASTM D5185m	>18	<b>5</b>	6	8
Copper	ppm	ASTM D5185m	>80	<b>14</b>	15	16
Tin	ppm	ASTM D5185m	>14	<b>4</b>	5	5
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	<b>4</b>	5	4
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0	3
Fuel		WC Method	>4.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>9.8</b>	9.7	10.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.8</b>	17.4	17.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	<b>1</b>	1	<1
Boron	ppm	ASTM D5185m		<b>32</b>	40	45
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>44</b>	49	51
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m		<b>12</b>	12	16
Calcium	ppm	ASTM D5185m		<b>3354</b>	3628	4056
Phosphorus	ppm	ASTM D5185m		<b>3</b>	2	7
Zinc	ppm	ASTM D5185m		<b>0</b>	0	0
Sulfur	ppm	ASTM D5185m		<b>2292</b>	2467	3051
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>10.7</b>	10.3	10.5
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	<b>9.30</b>	9.49	9.71
Visc @ 100°C	cSt	ASTM D445	15.5	<b>14.6</b>	14.6	14.6



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0061349 **Received** : 08 Jan 2024  
**Lab Number** : 06054127 **Diagnosed** : 09 Jan 2024  
**Unique Number** : 10820076 **Diagnostician** : Wes Davis  
**Test Package** : MAR 2

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**INGRAM BARGE**  
 900 S 3RD ST  
 PADUCAH, KY  
 US 42003

Contact: ANTHONY VAN CURA  
 anthony.vancura@ingrambarga.com  
 T: (270)415-4467  
 F: (615)695-3697