



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
Store 9 - Marietta
Machine Id
JOHN DEERE 750K 81220 (S/N 1T0750KXVJF335593)
Component
Transmission (Manual)
Fluid
JOHN DEERE HYDRAU (30 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		LEC0035546	LEC0025524	LEC0014658
Sample Date		Client Info		04 Jan 2024	27 Oct 2021	27 Jul 2020
Machine Age	hrs	Client Info		1513	894	437
Oil Age	hrs	Client Info		1513	0	437
Filter Age	hrs	Client Info		0	0	437
Oil Changed		Client Info		Not Changd	N/A	Not Changd
Filter Changed		Client Info		N/A	N/A	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>95	20	25	21
Iron	ppm	ASTM D5185m	>200	28	28	20
Chromium	ppm	ASTM D5185m	>5	0	0	<1
Nickel	ppm	ASTM D5185m	>5	<1	<1	2
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m	>7	0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	<1	0
Lead	ppm	ASTM D5185m	>45	<1	1	0
Copper	ppm	ASTM D5185m	>225	14	14	10
Tin	ppm	ASTM D5185m	>10	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>125	<1	2	2
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	<1	1
Boron	ppm	ASTM D5185m		0	5	<1
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		0	<1	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		0	2	2
Calcium	ppm	ASTM D5185m	87	91	91	96
Phosphorus	ppm	ASTM D5185m	727	634	579	617
Zinc	ppm	ASTM D5185m	900	830	829	806
Sulfur	ppm	ASTM D5185m	1500	1723	1468	1414
Visc @ 40°C	cSt	ASTM D445	65	57.2	57.6	59.1



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0035546 **Received** : 08 Jan 2024
Lab Number : 06054185 **Diagnosed** : 09 Jan 2024
Unique Number : 10820134 **Diagnostician** : Sean Felton
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

BRIDGEPORT EQUIPMENT & TOOL
 15 ACME ST
 MARIETTA, OH
 US 45750
 Contact: ROBBIE CLIFTON
 rclifton@bridgeportequip.com
 T: (740)373-6686
 F: (740)373-3895