



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
AMR-12th Street
 Machine Id
484145 116360
 Component
Swing Drive
 Fluid
LIEBHERR GEAR BASIC 90 LS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DJJ0020063	DJJ0018348	DJJ0019178
Sample Date		Client Info		02 Jan 2024	21 Sep 2023	01 Jun 2023
Machine Age	hrs	Client Info		9493	9001	8489
Oil Age	hrs	Client Info		0	0	500
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>400	61	▲ 490	82
Chromium	ppm	ASTM D5185m	>10	1	▲ 5	<1
Nickel	ppm	ASTM D5185m	>10	<1	<1	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>50	<1	2	0
Copper	ppm	ASTM D5185m	>200	40	▲ 313	36
Tin	ppm	ASTM D5185m	>10	3	▲ 8	2
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	MODER	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>50	2	4	<1
Potassium	ppm	ASTM D5185m	>20	1	4	<1
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	MODER	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		0	6	0
Boron	ppm	ASTM D5185m	0	0	<1	0
Barium	ppm	ASTM D5185m	0	0	0	2
Molybdenum	ppm	ASTM D5185m	0	<1	0	0
Manganese	ppm	ASTM D5185m	0	<1	2	<1
Magnesium	ppm	ASTM D5185m	<1	<1	5	0
Calcium	ppm	ASTM D5185m	<1	18	97	21
Phosphorus	ppm	ASTM D5185m	2143	2451	2683	2317
Zinc	ppm	ASTM D5185m	<1	0	30	14
Sulfur	ppm	ASTM D5185m	23468	37328	29362	32421
Visc @ 40°C	cSt	ASTM D445	170	194	193	185


Viscosity @ 40°C




Ferrous Alloys



Non-ferrous Metals



Viscosity @ 40°C



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DJJ0020063 **Received** : 08 Jan 2024
Lab Number : 06054409 **Diagnosed** : 09 Jan 2024
Unique Number : 10820358 **Diagnostician** : Wes Davis
Test Package : CONST

ADVANTAGE METALS RECYCLING - 12 STREET
 1153 S. 12TH STREET
 KANSAS CITY, KS
 US 66105
 Contact: JOHN PEEK
 john.peek@advantagerecycling.com
 T: (660)424-9134
 F: (913)621-2766

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)