



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
LILLIAN LOUISE
Component
Starboard Genset
Fluid
CHEVRON DELO 400 MULTIGRADE 15W40 (6 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0058043	MW0044281	MW0044276
Sample Date		Client Info		15 Dec 2023	02 Jun 2023	19 Jan 2023
Machine Age	hrs	Client Info		0	23560	22112
Oil Age	hrs	Client Info		500	485	496
Filter Age	hrs	Client Info		500	485	496
Oil Changed		Client Info		Changed	Changed	Not Changd
Filter Changed		Client Info		Changed	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>50	9	1	5
Chromium	ppm	ASTM D5185m	>4	0	<1	0
Nickel	ppm	ASTM D5185m	>2	<1	0	0
Titanium	ppm	ASTM D5185m		8	12	9
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>12	1	3	2
Lead	ppm	ASTM D5185m	>17	3	<1	<1
Copper	ppm	ASTM D5185m	>70	<1	2	<1
Tin	ppm	ASTM D5185m	>15	<1	1	<1
Vanadium	ppm	ASTM D5185m		<1	<1	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	5	5	4
Potassium	ppm	ASTM D5185m	>20	1	4	<1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844		0.4	0.2	0.2
Nitration	Abs/cm	*ASTM D7624	>20	9.2	9.1	8.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.0	20.3	19.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		5	3	2
Boron	ppm	ASTM D5185m		168	77	156
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		42	45	66
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		513	768	634
Calcium	ppm	ASTM D5185m		2427	1695	1554
Phosphorus	ppm	ASTM D5185m	1360	939	744	639
Zinc	ppm	ASTM D5185m	1480	1096	904	764
Sulfur	ppm	ASTM D5185m		3607	3895	3214
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.7	16.5	14.6
Base Number (BN)	mg KOH/g	ASTM D2896	12.2	7.3	7.2	8.0
Visc @ 100°C	cSt	ASTM D445	15.1	14.2	13.9	13.9



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0058043 **Received** : 08 Jan 2024
Lab Number : 06054592 **Diagnosed** : 10 Jan 2024
Unique Number : 10820541 **Diagnostician** : Sean Felton
Test Package : MAR 2

MAGNOLIA MARINE TRANSPORT
 697 HAINING ROAD
 VICKSBURG, MS
 US 39183
 Contact: MMT MAINTENANCE PLANNERS
 mmtmaintenanceplanners@ergon.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: x:
 F: (601)638-8028