



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
INTERNATIONAL I6312
Component
Diesel Engine
Fluid
MOBIL DELVAC 1300 SUPER15W40 (44 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		IL0012698	IL04810569	ILMFC27568
Sample Date		Client Info		11 Dec 2023	27 Sep 2019	30 Apr 2019
Machine Age	mls	Client Info		0	139530	14136
Oil Age	mls	Client Info		0	139530	14136
Filter Age	mls	Client Info		0	0	14136
Oil Changed		Client Info		Changed	N/A	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	20	6	12
Chromium	ppm	ASTM D5185m	>20	1	<1	2
Nickel	ppm	ASTM D5185m	>2	<1	0	<1
Titanium	ppm	ASTM D5185m	>2	<1	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	6	3	3
Lead	ppm	ASTM D5185m	>40	4	<1	0
Copper	ppm	ASTM D5185m	>330	1	<1	<1
Tin	ppm	ASTM D5185m	>15	1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	4	7
Potassium	ppm	ASTM D5185m	>20	10	2	7
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	0.6	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	12.2	8.6	9.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	24.5	23.9	23
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<1	2	4
Boron	ppm	ASTM D5185m	0	35	30	34
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	115	38	40
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	0	671	486	543
Calcium	ppm	ASTM D5185m		1329	1562	1721
Phosphorus	ppm	ASTM D5185m		693	660	733
Zinc	ppm	ASTM D5185m		896	797	880
Sulfur	ppm	ASTM D5185m		3249	1512	2005
Oxidation	Abs/.1mm	*ASTM D7414	>25	24.6	24.2	22.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	4.8	8.9	9.3
Visc @ 100°C	cSt	ASTM D445	14	12.9	13.2	13.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : IL0012698 **Received** : 09 Jan 2024
Lab Number : 06055278 **Diagnosed** : 10 Jan 2024
Unique Number : 10821227 **Diagnostician** : Wes Davis
Test Package : MOB1+

RUSH TRUCK LEASING - SALT LAKE CITY IDEALEASE
 964 SOUTH 3800 WEST, BLDG B
 SALT LAKE CITY, UT
 US 84104
 Contact: JAY ALEXANDER
 AlexanderJ1@RushEnterprises.com
 T:
 F: (801)977-9381

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)