



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**CAIRO (S/N 2080)**  
Component  
**Starboard Reduction Gear**  
Fluid  
**SCHAEFFER 209 MOLY UNIVERSAL GEARLUBE ISO 220 (150 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0062436</b>	MW0062374	MW0047412
Sample Date		Client Info		<b>27 Dec 2023</b>	20 Nov 2023	30 Oct 2023
Machine Age	hrs	Client Info		<b>48824</b>	47970	47535
Oil Age	hrs	Client Info		<b>48824</b>	47970	47535
Filter Age	hrs	Client Info		<b>48824</b>	47970	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>150	<b>54</b>	52	73
Chromium	ppm	ASTM D5185m	>10	<b>&lt;1</b>	2	2
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>0</b>	<1	<1
Silver	ppm	ASTM D5185m		<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>25	<b>3</b>	3	6
Lead	ppm	ASTM D5185m	>100	<b>0</b>	<1	<1
Copper	ppm	ASTM D5185m	>50	<b>8</b>	10	14
Tin	ppm	ASTM D5185m	>10	<b>0</b>	0	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	<b>8</b>	10	14
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	4	4
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>12</b>	9	12
Boron	ppm	ASTM D5185m	65	<b>16</b>	17	28
Barium	ppm	ASTM D5185m		<b>0</b>	5	8
Molybdenum	ppm	ASTM D5185m	325	<b>202</b>	220	313
Manganese	ppm	ASTM D5185m		<b>0</b>	1	<1
Magnesium	ppm	ASTM D5185m		<b>&lt;1</b>	4	5
Calcium	ppm	ASTM D5185m		<b>83</b>	86	119
Phosphorus	ppm	ASTM D5185m	875	<b>999</b>	924	1270
Zinc	ppm	ASTM D5185m		<b>65</b>	67	97
Sulfur	ppm	ASTM D5185m	16000	<b>15554</b>	19276	28862
Acid Number (AN)	mg KOH/g	ASTM D8045	2.5	<b>2.31</b>	2.53	2.42
Visc @ 40°C	cSt	ASTM D445	219	<b>268</b>	265	262



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0062436 **Received** : 09 Jan 2024  
**Lab Number** : 06055506 **Diagnosed** : 10 Jan 2024  
**Unique Number** : 10821455 **Diagnostician** : Sean Felton  
**Test Package** : MAR 2

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**AMERICAN COMMERCIAL LINES**  
 PO BOX 610, 1701 E. MARKET STREET  
 JEFFERSONVILLE, IN  
 US 47130  
 Contact: RONALD SCHNEIDER  
 ronald.schneider@bargeacbl.com  
 T:  
 F: (812)288-1644