



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
VOLVO A40G 342685
Component
Rear Axle
Fluid
{not provided} (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

WEAR

All component wear rates are normal.










CONTAMINATION

There is no indication of any contamination in the oil.

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP0008132	VCP268281	---
Sample Date		Client Info		05 Jan 2024	02 Sep 2020	---
Machine Age	hrs	Client Info		0	2193	---
Oil Age	hrs	Client Info		0	0	---
Filter Age	hrs	Client Info		0	0	---
Oil Changed		Client Info		N/A	Not Changd	---
Filter Changed		Client Info		N/A	Not Changd	---
Sample Status				NORMAL	NORMAL	---
Iron	ppm	ASTM D5185m	>900	76	564	---
Chromium	ppm	ASTM D5185m	>20	1	5	---
Nickel	ppm	ASTM D5185m	>10	0	2	---
Titanium	ppm	ASTM D5185m		0	0	---
Silver	ppm	ASTM D5185m		0	<1	---
Aluminum	ppm	ASTM D5185m	>30	<1	2	---
Lead	ppm	ASTM D5185m	>50	<1	<1	---
Copper	ppm	ASTM D5185m	>150	<1	5	---
Tin	ppm	ASTM D5185m	>20	<1	<1	---
Vanadium	ppm	ASTM D5185m		0	<1	---
White Metal	scalar	*Visual	NONE	LIGHT	MODER	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---
Silicon	ppm	ASTM D5185m	>50	6	10	---
Potassium	ppm	ASTM D5185m	>20	0	6	---
Water		WC Method	>0.2	NEG	NEG	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---
Sodium	ppm	ASTM D5185m		1	4	---
Boron	ppm	ASTM D5185m		69	150	---
Barium	ppm	ASTM D5185m		0	5	---
Molybdenum	ppm	ASTM D5185m		58	3	---
Manganese	ppm	ASTM D5185m		2	12	---
Magnesium	ppm	ASTM D5185m		805	0	---
Calcium	ppm	ASTM D5185m		1015	37	---
Phosphorus	ppm	ASTM D5185m		1052	2092	---
Zinc	ppm	ASTM D5185m		1109	27	---
Sulfur	ppm	ASTM D5185m		5140	25056	---
Visc @ 40°C	cSt	ASTM D445		78.3	50.7	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP0008132 **Received** : 09 Jan 2024
Lab Number : 06055656 **Diagnosed** : 10 Jan 2024
Unique Number : 10821605 **Diagnostician** : Jonathan Hester
Test Package : MOBCE

ALTA EQUIPMENT COMPANY
 8750 PHILIPS HWY
 JACKSONVILLE, FL
 US 32256

Contact: TECHNICIAN ACCOUNT
 catherine.anastasio@wearcheck.com

T:
 F: (904)737-1260

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)