



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	ATTENTION



Machine Id
MACK 812100
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		GFL0109064	GFL0109060	GFL0086193
Sample Date		Client Info		05 Jan 2024	05 Jan 2024	27 Sep 2023
Machine Age	hrs	Client Info		6168	6168	5362
Oil Age	hrs	Client Info		0	6168	5477
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ATTENTION	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	7	19	2
Chromium	ppm	ASTM D5185m	>20	<1	1	0
Nickel	ppm	ASTM D5185m	>5	0	2	0
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	2	0
Lead	ppm	ASTM D5185m	>40	0	<1	<1
Copper	ppm	ASTM D5185m	>330	<1	3	<1
Tin	ppm	ASTM D5185m	>15	0	1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>25	3	7	2
Potassium	ppm	ASTM D5185m	>20	3	3	<1
Fuel	%	ASTM D3524	>3.0	<1.0	0.2	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>4	0.4	0.6	0.1
Nitration	Abs/cm	*ASTM D7624	>20	7.5	8.3	4.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.7	19.9	16.3
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION


The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

Sodium	ppm	ASTM D5185m		3	0	1
Boron	ppm	ASTM D5185m	0	20	10	29
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	60	76	62
Manganese	ppm	ASTM D5185m	0	0	<1	<1
Magnesium	ppm	ASTM D5185m	1010	722	912	788
Calcium	ppm	ASTM D5185m	1070	1106	1445	1071
Phosphorus	ppm	ASTM D5185m	1150	934	994	912
Zinc	ppm	ASTM D5185m	1270	1096	1376	1132
Sulfur	ppm	ASTM D5185m	2060	2986	3527	2961
Oxidation	Abs/.1mm	*ASTM D7414	>25	13.4	13.8	11.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	7.2	5.5	8.1
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.1	▲ 12.0	12.7


▲ Viscosity @ 100°C




Ferrous Alloys



Base Number




Non-ferrous Metals




Fuel Dilution



▲ Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0109064 **Received** : 09 Jan 2024
Lab Number : 06055760 **Diagnosed** : 11 Jan 2024
Unique Number : 10821709 **Diagnostician** : Jonathan Hester
Test Package : FLEET (Additional Tests: FUELDILUTION, PercentFuel)

GFL Environmental - 009 - Fairburn
 6905 Roosevelt Hwy
 Fairburn, GA
 US 30213
 Contact: Eric Jones
 erjones@gflenv.com
 T: (678)630-9927
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)