



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
MEV
Machine Id
MEV (S/N 1008)
Component
Port Main Engine
Fluid
CHEVRON DELO 710 LS (350 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		MW0055094	MW0058951	MW0043842
Sample Date		Client Info		27 Dec 2023	19 Dec 2023	30 Sep 2023
Machine Age	hrs	Client Info		87292	0	85182
Oil Age	hrs	Client Info		41194	0	39054
Filter Age	hrs	Client Info		1032	0	1145
Oil Changed		Client Info		Not Chngd	Changed	Not Chngd
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	27	8	25
Chromium	ppm	ASTM D5185m	>8	1	0	1
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	2	<1	2
Lead	ppm	ASTM D5185m	>18	10	7	9
Copper	ppm	ASTM D5185m	>80	29	▲ 556	30
Tin	ppm	ASTM D5185m	>14	6	<1	6
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	3	3	2
Potassium	ppm	ASTM D5185m	>20	<1	3	<1
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.5	0.1	0.6
Nitration	Abs/cm	*ASTM D7624	>20	9.3	7.6	9.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.4	20.6	18.9
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	<1	11	2
Boron	ppm	ASTM D5185m		33	110	30
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		46	3	44
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		12	237	13
Calcium	ppm	ASTM D5185m		3572	1801	3304
Phosphorus	ppm	ASTM D5185m		6	1041	7
Zinc	ppm	ASTM D5185m		0	1212	0
Sulfur	ppm	ASTM D5185m		2263	3345	2044
Oxidation	Abs/.1mm	*ASTM D7414	>25	12.4	18.0	12.7
Base Number (BN)	mg KOH/g	ASTM D2896	10.5	5.9	6.5	5.8
Visc @ 100°C	cSt	ASTM D445	15.5	14.9	13.4	14.5



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : MW0055094 **Received** : 10 Jan 2024
Lab Number : 06056316 **Diagnosed** : 11 Jan 2024
Unique Number : 10822265 **Diagnostician** : Jonathan Hester
Test Package : MAR 2

AMERICAN RIVER TRANSPORTATION CO.
P.O. BOX 2889
ST. LOUIS, MO
US 63111
Contact: BRIAN GRIEWING
brian.griewing@adm.com
T:
F: (314)481-5278

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)