



|                 |               |
|-----------------|---------------|
| WEAR            | <b>NORMAL</b> |
| CONTAMINATION   | <b>NORMAL</b> |
| FLUID CONDITION | <b>NORMAL</b> |

Area  
**SAR**  
Machine Id  
**SAR (S/N 09-01-1031)**  
Component  
**Port Main Engine**  
Fluid  
**CHEVRON DELO 710 LS (400 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

| Test           | UOM | Method      | Limit/Abn | Current            | History1    | History2    |
|----------------|-----|-------------|-----------|--------------------|-------------|-------------|
| Sample Number  |     | Client Info |           | <b>MW0060833</b>   | MW0050833   | MW0050841   |
| Sample Date    |     | Client Info |           | <b>13 Dec 2023</b> | 23 Sep 2023 | 14 Jul 2023 |
| Machine Age    | hrs | Client Info |           | <b>17402</b>       | 15112       | 13855       |
| Oil Age        | hrs | Client Info |           | <b>4276</b>        | 6987        | 5730        |
| Filter Age     | hrs | Client Info |           | <b>1180</b>        | 1274        | 1115        |
| Oil Changed    |     | Client Info |           | <b>Changed</b>     | Not Changed | Not Changed |
| Filter Changed |     | Client Info |           | <b>Changed</b>     | Changed     | Changed     |
| Sample Status  |     |             |           | <b>NORMAL</b>      | NORMAL      | NORMAL      |

**WEAR**

All component wear rates are normal.

|              |        |             |      |              |      |      |
|--------------|--------|-------------|------|--------------|------|------|
| Iron         | ppm    | ASTM D5185m | >75  | <b>7</b>     | 7    | 5    |
| Chromium     | ppm    | ASTM D5185m | >8   | <b>&lt;1</b> | <1   | <1   |
| Nickel       | ppm    | ASTM D5185m | >2   | <b>0</b>     | 0    | 0    |
| Titanium     | ppm    | ASTM D5185m | >3   | <b>0</b>     | <1   | 0    |
| Silver       | ppm    | ASTM D5185m | >2   | <b>0</b>     | 0    | 0    |
| Aluminum     | ppm    | ASTM D5185m | >15  | <b>1</b>     | 2    | 2    |
| Lead         | ppm    | ASTM D5185m | >18  | <b>1</b>     | 1    | <1   |
| Copper       | ppm    | ASTM D5185m | >80  | <b>5</b>     | 5    | 3    |
| Tin          | ppm    | ASTM D5185m | >14  | <b>2</b>     | 2    | 1    |
| Vanadium     | ppm    | ASTM D5185m |      | <b>0</b>     | <1   | 0    |
| White Metal  | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |
| Yellow Metal | scalar | *Visual     | NONE | <b>NONE</b>  | NONE | NONE |

**CONTAMINATION**







There is no indication of any contamination in the oil.

|                  |          |             |       |                |       |       |
|------------------|----------|-------------|-------|----------------|-------|-------|
| Silicon          | ppm      | ASTM D5185m | >20   | <b>2</b>       | 3     | 3     |
| Potassium        | ppm      | ASTM D5185m | >20   | <b>&lt;1</b>   | 2     | 1     |
| Fuel             |          | WC Method   | >4.0  | <b>&lt;1.0</b> | <1.0  | <1.0  |
| Water            |          | WC Method   | >0.1  | <b>NEG</b>     | NEG   | NEG   |
| Glycol           |          | WC Method   |       | <b>NEG</b>     | NEG   | NEG   |
| Soot %           | %        | *ASTM D7844 | >3    | <b>0.3</b>     | 0.4   | 0.2   |
| Nitration        | Abs/cm   | *ASTM D7624 | >20   | <b>7.7</b>     | 7.8   | 6.7   |
| Sulfation        | Abs/.1mm | *ASTM D7415 | >30   | <b>16.5</b>    | 16.2  | 14.5  |
| Silt             | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Debris           | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Sand/Dirt        | scalar   | *Visual     | NONE  | <b>NONE</b>    | NONE  | NONE  |
| Appearance       | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Odor             | scalar   | *Visual     | NORML | <b>NORML</b>   | NORML | NORML |
| Emulsified Water | scalar   | *Visual     | >0.1  | <b>NEG</b>     | NEG   | NEG   |

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

|                  |          |             |      |              |      |      |
|------------------|----------|-------------|------|--------------|------|------|
| Sodium           | ppm      | ASTM D5185m | >75  | <b>1</b>     | 2    | 0    |
| Boron            | ppm      | ASTM D5185m |      | <b>40</b>    | 39   | 42   |
| Barium           | ppm      | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| Molybdenum       | ppm      | ASTM D5185m |      | <b>44</b>    | 43   | 44   |
| Manganese        | ppm      | ASTM D5185m |      | <b>&lt;1</b> | <1   | <1   |
| Magnesium        | ppm      | ASTM D5185m |      | <b>11</b>    | 0    | 8    |
| Calcium          | ppm      | ASTM D5185m |      | <b>3475</b>  | 3274 | 3295 |
| Phosphorus       | ppm      | ASTM D5185m |      | <b>4</b>     | 0    | 2    |
| Zinc             | ppm      | ASTM D5185m |      | <b>0</b>     | 0    | 0    |
| Sulfur           | ppm      | ASTM D5185m |      | <b>2212</b>  | 1769 | 2174 |
| Oxidation        | Abs/.1mm | *ASTM D7414 | >25  | <b>10.6</b>  | 9.3  | 8.1  |
| Base Number (BN) | mg KOH/g | ASTM D2896  | 10.5 | <b>6.4</b>   | 6.8  | 6.3  |
| Visc @ 100°C     | cSt      | ASTM D445   | 15.5 | <b>14.6</b>  | 14.4 | 14.7 |



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0060833 **Received** : 10 Jan 2024  
**Lab Number** : 06056342 **Diagnosed** : 11 Jan 2024  
**Unique Number** : 10822291 **Diagnostician** : Wes Davis  
**Test Package** : MAR 2

**AMERICAN RIVER TRANSPORTATION CO.**  
 P.O. BOX 2889  
 ST. LOUIS, MO  
 US 63111  
 Contact: BRIAN GRIEWING  
 brian.griewing@adm.com  
 T:  
 F: (314)481-5278

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)