



VOLVO

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Area
[646180]
Machine Id
VOLVO EC300EL 20-516 (S/N 312274)
Component
Diesel Engine
Fluid
VOLVO ULTRA DIESEL ENGINE OIL 15W40 VDS-3 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		VCP452280	VCP341345	VCP258470
Sample Date		Client Info		19 Dec 2023	08 Jun 2022	11 Sep 2019
Machine Age	hrs	Client Info		4751	3281	1330
Oil Age	hrs	Client Info		500	500	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	13	12	8
Chromium	ppm	ASTM D5185m	>10	<1	<1	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	1
Titanium	ppm	ASTM D5185m		<1	92	<1
Silver	ppm	ASTM D5185m	>2	0	<1	<1
Aluminum	ppm	ASTM D5185m	>10	5	▲ 10	4
Lead	ppm	ASTM D5185m	>20	2	3	0
Copper	ppm	ASTM D5185m	>15	5	▲ 17	2
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	6	8	10
Potassium	ppm	ASTM D5185m	>20	3	14	8
Fuel		WC Method	>6.0	<1.0	1.2	<1.0
Water		WC Method	>0.1	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.2	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	8.0	8.3	6.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.4	19.9	21.4
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		1	2	3
Boron	ppm	ASTM D5185m	2.5	10	166	48
Barium	ppm	ASTM D5185m	0.0	0	<1	0
Molybdenum	ppm	ASTM D5185m	0.7	62	<1	39
Manganese	ppm	ASTM D5185m	0.0	<1	<1	<1
Magnesium	ppm	ASTM D5185m	256	882	400	490
Calcium	ppm	ASTM D5185m	2057	1162	1763	1586
Phosphorus	ppm	ASTM D5185m	935	1049	1049	737
Zinc	ppm	ASTM D5185m	1223	1273	1265	840
Sulfur	ppm	ASTM D5185m	4079	3110	3847	2171
Oxidation	Abs/.1mm	*ASTM D7414	>25	15.3	15.7	19.5
Base Number (BN)	mg KOH/g	ASTM D2896	10	8.8	8.9	---
Visc @ 100°C	cSt	ASTM D445	15.0	13.1	▲ 11.7	12.8



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : VCP452280 **Received** : 10 Jan 2024
Lab Number : 06056457 **Diagnosed** : 11 Jan 2024
Unique Number : 10822406 **Diagnostician** : Don Baldridge
Test Package : MOB 1 (Additional Tests: TBN)

ADAMO DEMOLITION COMPANY
 320 EAST 7 MILE RD
 DETROIT, MI
 US 48203
 Contact: SERVICE MANAGER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: