



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
LIEBHERR A944C CAR SIDE 4 - LIEBHERR (S/N 027895-744)
Component
Diesel Engine
Fluid
UNITED OIL DURALENE (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		DC0033381	DC0029670	DC0030627
Sample Date		Client Info		20 Dec 2023	22 Oct 2023	14 Sep 2023
Machine Age	hrs	Client Info		250	250	250
Oil Age	hrs	Client Info		0	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Filter Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	10	6	4
Chromium	ppm	ASTM D5185m	>5	<1	0	<1
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>3	0	<1	0
Aluminum	ppm	ASTM D5185m	>15	2	2	<1
Lead	ppm	ASTM D5185m	>30	5	1	0
Copper	ppm	ASTM D5185m	>125	2	1	<1
Tin	ppm	ASTM D5185m	>5	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>60	6	7	6
Potassium	ppm	ASTM D5185m	>20	<1	3	<1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	9.9	8.7	8.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.4	20.1	19.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		2	0	3
Boron	ppm	ASTM D5185m		6	4	3
Barium	ppm	ASTM D5185m		0	4	0
Molybdenum	ppm	ASTM D5185m		6	3	<1
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		89	44	49
Calcium	ppm	ASTM D5185m		2560	2548	2722
Phosphorus	ppm	ASTM D5185m		1016	990	1000
Zinc	ppm	ASTM D5185m		1252	1139	1232
Sulfur	ppm	ASTM D5185m		3844	4318	4381
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.7	14.4	13.9
Base Number (BN)	mg KOH/g	ASTM D2896		4.8	6.8	6.6
Visc @ 100°C	cSt	ASTM D445		13.7	13.6	13.7



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : DC0033381 **Received** : 10 Jan 2024
Lab Number : 06056478 **Diagnosed** : 11 Jan 2024
Unique Number : 10822427 **Diagnostician** : Don Baldridge
Test Package : MOB 1 (Additional Tests: TBN)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

SIMS ARG
 3100 WEEDON STREET
 BALTIMORE, MD
 US 21226
 Contact: MARK NUZZO
 mark.nuzzo@simsmm.com
 T: (410)355-1488
 F: (410)355-5423