



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 210G 1FF210GXCMF529131

Component
Left Final Drive

Fluid
JOHN DEERE GL-5 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0188520	JR0188697	JR0161220
Sample Date		Client Info		05 Jan 2024	19 Sep 2023	04 May 2023
Machine Age	hrs	Client Info		4264	3648	2991
Oil Age	hrs	Client Info		2569	2610	2478
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184	>1250	145	36	37
Iron	ppm	ASTM D5185m	>750	362	78	95
Chromium	ppm	ASTM D5185m	>9	3	0	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>40	0	1	<1
Lead	ppm	ASTM D5185m	>15	0	0	0
Copper	ppm	ASTM D5185m	>40	<1	<1	0
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	12	8	9
Potassium	ppm	ASTM D5185m	>20	2	<1	2
Water		WC Method	>0.075	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.075	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	<1	1	0
Boron	ppm	ASTM D5185m		121	59	175
Barium	ppm	ASTM D5185m		1	0	0
Molybdenum	ppm	ASTM D5185m		7	0	4
Manganese	ppm	ASTM D5185m		4	<1	<1
Magnesium	ppm	ASTM D5185m		26	2	20
Calcium	ppm	ASTM D5185m		31	7	27
Phosphorus	ppm	ASTM D5185m		830	984	931
Zinc	ppm	ASTM D5185m		49	0	15
Sulfur	ppm	ASTM D5185m		15837	23700	23043
Visc @ 40°C	cSt	ASTM D445		149.7	142	150



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0188520 **Received** : 10 Jan 2024
Lab Number : 06056912 **Diagnosed** : 12 Jan 2024
Unique Number : 10822861 **Diagnostician** : Jonathan Hester
Test Package : CONST (Additional Tests: PQ)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)