



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**JOHN DEERE 644K 1DW644KZAJF690443**

Component  
**Front Differential**

Fluid  
**JOHN DEERE HY-GARD HYD/TRANS (6 GAL)**

### RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>JR0193598</b>	JR0173798	JR0154854
Sample Date		Client Info		<b>04 Jan 2024</b>	06 Jun 2023	01 Feb 2023
Machine Age	hrs	Client Info		<b>7050</b>	6529	6101
Oil Age	hrs	Client Info		<b>1000</b>	428	2001
Filter Age	hrs	Client Info		<b>1000</b>	0	1001
Oil Changed		Client Info		<b>Not Changed</b>	Not Changed	Changed
Filter Changed		Client Info		<b>Changed</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

### WEAR

All component wear rates are normal.

PQ		ASTM D8184	>135	<b>20</b>	15	14
Iron	ppm	ASTM D5185m	>420	<b>30</b>	23	50
Chromium	ppm	ASTM D5185m	>4	<b>0</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m		<b>0</b>	0	0
Silver	ppm	ASTM D5185m		<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>5	<b>0</b>	0	<1
Lead	ppm	ASTM D5185m	>95	<b>40</b>	28	77
Copper	ppm	ASTM D5185m	>170	<b>17</b>	11	31
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

### CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>35	<b>2</b>	4	3
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	0	<1
Water		WC Method	>.2	<b>NEG</b>	NEG	NEG
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	<b>NEG</b>	NEG	NEG

### FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<b>2</b>	2	4
Boron	ppm	ASTM D5185m	6	<b>6</b>	1	<1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	<1
Molybdenum	ppm	ASTM D5185m	0	<b>0</b>	<1	2
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	145	<b>86</b>	92	82
Calcium	ppm	ASTM D5185m	3570	<b>3116</b>	3269	3002
Phosphorus	ppm	ASTM D5185m	1290	<b>973</b>	1014	904
Zinc	ppm	ASTM D5185m	1640	<b>1160</b>	1238	1076
Sulfur	ppm	ASTM D5185m		<b>3565</b>	4332	3814
Visc @ 40°C	cSt	ASTM D445	57.0	<b>54.0</b>	54.9	52.6



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : JR0193598 **Received** : 10 Jan 2024  
**Lab Number** : 06056932 **Diagnosed** : 11 Jan 2024  
**Unique Number** : 10822881 **Diagnostician** : Don Baldrige  
**Test Package** : CONST ( Additional Tests: PQ )

**MORTON TRUCKING**  
 121 GARNET LANE  
 JACKSONVILLE, NC  
 US 28546  
 Contact: TIM MORTON  
 timm@timmortontrucking.com  
 T: (252)322-4031  
 F: (252)322-5215

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)