



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Area  
**MONTGOMERY**  
Machine Id  
**420046**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0081891</b>	GFL0091308	GFL0091300
Sample Date		Client Info		<b>05 Jan 2024</b>	28 Dec 2023	08 Dec 2023
Machine Age	mls	Client Info		<b>112085</b>	110483	9105
Oil Age	mls	Client Info		<b>1602</b>	100780	1220
Filter Age	mls	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Changed	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>3</b>	8	8
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	2	3
Lead	ppm	ASTM D5185m	>40	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m	>330	<b>0</b>	2	1
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>4</b>	8	8
Potassium	ppm	ASTM D5185m	>20	<b>2</b>	4	2
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.1</b>	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>5.2</b>	7.8	8.4
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>17.9</b>	18.8	19.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>3</b>	3	3
Boron	ppm	ASTM D5185m	0	<b>3</b>	2	2
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>67</b>	62	60
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>1101</b>	992	982
Calcium	ppm	ASTM D5185m	1070	<b>1151</b>	1113	1041
Phosphorus	ppm	ASTM D5185m	1150	<b>1159</b>	972	1009
Zinc	ppm	ASTM D5185m	1270	<b>1386</b>	1315	1289
Sulfur	ppm	ASTM D5185m	2060	<b>3852</b>	2984	2756
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.8</b>	15.3	16.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.7</b>	7.8	6.7
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.9</b>	13.6	13.1



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0081891 **Received** : 10 Jan 2024  
**Lab Number** : 06057297 **Diagnosed** : 11 Jan 2024  
**Unique Number** : 10823246 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

GFL Environmental - 172 - Montgomery-Alexander City-Tallahassee  
 Multiple Sites  
 Montgomery, AL  
 US 36108  
 Contact: RICHARD HATFIELD  
 rhatfield@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: