



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
781-193

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 40 (--- LTR)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		RPL06057319	RPL05903569	RPL05799553
Sample Date		Client Info		05 Jan 2024	14 Jul 2023	12 Mar 2023
Machine Age	mls	Client Info		224185	170767	140445
Oil Age	mls	Client Info		5560	68423	3475
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	35	39	7
Chromium	ppm	ASTM D5185m	>20	<1	<1	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	6	▲ 9	1
Lead	ppm	ASTM D5185m	>40	0	0	0
Copper	ppm	ASTM D5185m	>330	5	5	<1
Tin	ppm	ASTM D5185m	>15	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	17	▲ 37	7
Potassium	ppm	ASTM D5185m	>20	7	15	1
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.8	0.8	0.7
Nitration	Abs/cm	*ASTM D7624	>20	11.9	11.8	11.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	28.3	27.6	26.7
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>216	1	2	1
Boron	ppm	ASTM D5185m	250	52	43	137
Barium	ppm	ASTM D5185m	10	0	0	0
Molybdenum	ppm	ASTM D5185m	100	134	124	114
Manganese	ppm	ASTM D5185m		0	<1	1
Magnesium	ppm	ASTM D5185m	450	690	745	508
Calcium	ppm	ASTM D5185m	3000	1661	1714	1509
Phosphorus	ppm	ASTM D5185m	1150	756	774	811
Zinc	ppm	ASTM D5185m	1350	889	981	1008
Sulfur	ppm	ASTM D5185m	4250	2679	3060	2909
Oxidation	Abs/.1mm	*ASTM D7414	>25	27.9	25.3	23.6
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	4.6	5.3	6.2
Visc @ 100°C	cSt	ASTM D445	14.4	14.4	14.5	14.2



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RPL06057319 **Received** : 10 Jan 2024
Lab Number : 06057319 **Diagnosed** : 12 Jan 2024
Unique Number : 10823268 **Diagnostician** : Sean Felton
Test Package : FLEET

RTL PACLEASE - 7050 -Leasing Tyler
 10791 Hwy 69 North
 Tyler, TX
 US 75706
 Contact: Justin Cooper
 CooperJ1@RushEnterprises.Com
 T: (903)405-3000
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)