



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**4569M**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0110012</b>	GFL0104277	GFL0059311
Sample Date		Client Info		<b>08 Jan 2024</b>	27 Dec 2023	30 Nov 2023
Machine Age	hrs	Client Info		<b>9202</b>	9085	8930
Oil Age	hrs	Client Info		<b>8890</b>	8928	157
Filter Age	hrs	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>N/A</b>	N/A	N/A
Filter Changed		Client Info		<b>N/A</b>	N/A	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	<b>14</b>	20	13
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>1</b>	4	2
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	0	2
Copper	ppm	ASTM D5185m	>330	<b>&lt;1</b>	1	5
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>4</b>	10	5
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	2	3
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>0.6</b>	0.2	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.2</b>	5.2	5.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>20.8</b>	17.4	17.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>4</b>	5	0
Boron	ppm	ASTM D5185m	0	<b>0</b>	5	13
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>54</b>	57	67
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>917</b>	918	902
Calcium	ppm	ASTM D5185m	1070	<b>1005</b>	1066	1287
Phosphorus	ppm	ASTM D5185m	1150	<b>934</b>	1029	1123
Zinc	ppm	ASTM D5185m	1270	<b>1249</b>	1235	1311
Sulfur	ppm	ASTM D5185m	2060	<b>2821</b>	3186	3837
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>19.5</b>	13.1	13.6
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>8.1</b>	9.6	9.4
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.7</b>	13.9	14.5



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0110012 **Received** : 11 Jan 2024  
**Lab Number** : 06057769 **Diagnosed** : 12 Jan 2024  
**Unique Number** : 10829151 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 410 - Michigan West**  
 39000 Van Born Rd  
 Wayne, MI  
 US 48184

Contact: Belal Dgheish  
 bdgheish@gflenv.com  
 T: (734)714-2340

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: