



OIL ANALYSIS REPORT

| | |
|-----------------|--------|
| WEAR | NORMAL |
| CONTAMINATION | NORMAL |
| FLUID CONDITION | NORMAL |



Area
Store 5 - Cross Lanes
Machine Id
JOHN DEERE 850L 1T0850LXEMF399825
Component
Right Inner Final Drive
Fluid
JOHN DEERE HY-GARD HYD/TRANS (5 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

| Test | UOM | Method | Limit/Abn | Current | History1 | History2 |
|----------------|-----|-------------|-----------|-------------|----------|----------|
| Sample Number | | Client Info | | LEC0046550 | --- | --- |
| Sample Date | | Client Info | | 09 Jan 2024 | --- | --- |
| Machine Age | hrs | Client Info | | 2577 | --- | --- |
| Oil Age | hrs | Client Info | | 1100 | --- | --- |
| Filter Age | hrs | Client Info | | 0 | --- | --- |
| Oil Changed | | Client Info | | Not Changd | --- | --- |
| Filter Changed | | Client Info | | N/A | --- | --- |
| Sample Status | | | | NORMAL | --- | --- |

WEAR

All component wear rates are normal.

| | | | | | | |
|--------------|--------|-------------|-------|------|-----|-----|
| PQ | | ASTM D8184 | >1250 | 17 | --- | --- |
| Iron | ppm | ASTM D5185m | >750 | 16 | --- | --- |
| Chromium | ppm | ASTM D5185m | >9 | 0 | --- | --- |
| Nickel | ppm | ASTM D5185m | >10 | 0 | --- | --- |
| Titanium | ppm | ASTM D5185m | | 0 | --- | --- |
| Silver | ppm | ASTM D5185m | | 0 | --- | --- |
| Aluminum | ppm | ASTM D5185m | >40 | 0 | --- | --- |
| Lead | ppm | ASTM D5185m | >15 | <1 | --- | --- |
| Copper | ppm | ASTM D5185m | >40 | 0 | --- | --- |
| Tin | ppm | ASTM D5185m | >10 | 0 | --- | --- |
| Vanadium | ppm | ASTM D5185m | | 0 | --- | --- |
| White Metal | scalar | *Visual | NONE | NONE | --- | --- |
| Yellow Metal | scalar | *Visual | NONE | NONE | --- | --- |

CONTAMINATION







There is no indication of any contamination in the oil.

| | | | | | | |
|------------------|--------|-------------|--------|-------|-----|-----|
| Silicon | ppm | ASTM D5185m | >75 | 5 | --- | --- |
| Potassium | ppm | ASTM D5185m | >20 | 0 | --- | --- |
| Water | | WC Method | >0.075 | NEG | --- | --- |
| Silt | scalar | *Visual | NONE | NONE | --- | --- |
| Debris | scalar | *Visual | NONE | NONE | --- | --- |
| Sand/Dirt | scalar | *Visual | NONE | NONE | --- | --- |
| Appearance | scalar | *Visual | NORML | NORML | --- | --- |
| Odor | scalar | *Visual | NORML | NORML | --- | --- |
| Emulsified Water | scalar | *Visual | >0.075 | NEG | --- | --- |

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

| | | | | | | |
|-------------|-----|-------------|------|------|-----|-----|
| Sodium | ppm | ASTM D5185m | >51 | 0 | --- | --- |
| Boron | ppm | ASTM D5185m | 6 | 1 | --- | --- |
| Barium | ppm | ASTM D5185m | 0 | 0 | --- | --- |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | --- | --- |
| Manganese | ppm | ASTM D5185m | | 0 | --- | --- |
| Magnesium | ppm | ASTM D5185m | 145 | 103 | --- | --- |
| Calcium | ppm | ASTM D5185m | 3570 | 3445 | --- | --- |
| Phosphorus | ppm | ASTM D5185m | 1290 | 943 | --- | --- |
| Zinc | ppm | ASTM D5185m | 1640 | 1276 | --- | --- |
| Sulfur | ppm | ASTM D5185m | | 3405 | --- | --- |
| Visc @ 40°C | cSt | ASTM D445 | 57.0 | 45.9 | --- | --- |



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : LEC0046550 **Received** : 11 Jan 2024
Lab Number : 06058336 **Diagnosed** : 12 Jan 2024
Unique Number : 10829718 **Diagnostician** : Wes Davis
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

LESLIE EQUIPMENT COMPANY
 105 TENNIS CENTER DR.
 MARIETTA, OH
 US 45750-9765
 Contact: LEANNE KENDALL
 KendalLeanne@lec1.com
 T:
 F: (740)373-5570