



ASCENDUM

OIL ANALYSIS REPORT

WEAR	ABNORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
VOLVO EC350 314312
Component
Front Left Final Drive
Fluid
GEAR OIL SAE 80W140 (--- GAL)

RECOMMENDATION

The oil change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		ASC0006501	VCP426648	VCP403220
Sample Date		Client Info		15 Dec 2023	24 May 2023	27 Dec 2022
Machine Age	hrs	Client Info		3891	2748	2030
Oil Age	hrs	Client Info		1143	0	0
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	NORMAL

WEAR

The iron level has decreased, but is still abnormal. All other component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	▲ 564	▲ 921	480
Chromium	ppm	ASTM D5185m	>10	8	▲ 14	6
Nickel	ppm	ASTM D5185m	>10	<1	1	<1
Titanium	ppm	ASTM D5185m		<1	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	9	12	4
Lead	ppm	ASTM D5185m	>25	0	0	<1
Copper	ppm	ASTM D5185m	>50	2	1	<1
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	MODER	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION






There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	35	57	13
Potassium	ppm	ASTM D5185m	>20	1	2	0
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	LIGHT	MODER	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		<1	1	1
Boron	ppm	ASTM D5185m	400	60	0	2
Barium	ppm	ASTM D5185m	200	0	2	0
Molybdenum	ppm	ASTM D5185m	12	<1	2	1
Manganese	ppm	ASTM D5185m		5	8	4
Magnesium	ppm	ASTM D5185m	12	2	6	5
Calcium	ppm	ASTM D5185m	150	12	34	15
Phosphorus	ppm	ASTM D5185m	1650	846	451	484
Zinc	ppm	ASTM D5185m	125	2	27	21
Sulfur	ppm	ASTM D5185m	22500	24848	19309	19558
Visc @ 40°C	cSt	ASTM D445	263	239	147	146



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : ASC0006501 **Received** : 11 Jan 2024
Lab Number : 06058467 **Diagnosed** : 14 Jan 2024
Unique Number : 10829849 **Diagnostician** : Don Baldrige
Test Package : CONST

113 - ASCENDUM MACHINERY INC - GARNER
 3561 JONES SAUSAGE ROAD
 GARNER, NC
 US 27529
 Contact: TRENT BROADWELL
 trent.broadwell@ascendummachinery.com
 T: (919)661-8817
 F: (919)661-9038

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)