



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**927042**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0104547</b>	GFL0092613	GFL0082534
Sample Date		Client Info		<b>08 Jan 2024</b>	01 Nov 2023	21 Jul 2023
Machine Age	hrs	Client Info		<b>17479</b>	17119	16559
Oil Age	hrs	Client Info		<b>920</b>	560	607
Filter Age	hrs	Client Info		<b>920</b>	560	607
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Changed
Filter Changed		Client Info		<b>N/A</b>	N/A	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>20</b>	23	10
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>&lt;1</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>2</b>	3	2
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	1	0
Copper	ppm	ASTM D5185m	>330	<b>3</b>	1	0
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>5</b>	5	5
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	1	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>0.5</b>	0.9	0.5
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.8</b>	8.6	7.0
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>19.9</b>	21.1	19.8
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>36</b>	4	4
Boron	ppm	ASTM D5185m	0	<b>2</b>	7	2
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>57</b>	62	65
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	0	<1
Magnesium	ppm	ASTM D5185m	1010	<b>913</b>	952	1059
Calcium	ppm	ASTM D5185m	1070	<b>994</b>	1073	1146
Phosphorus	ppm	ASTM D5185m	1150	<b>980</b>	958	1096
Zinc	ppm	ASTM D5185m	1270	<b>1155</b>	1220	1353
Sulfur	ppm	ASTM D5185m	2060	<b>2969</b>	3028	3723
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>15.6</b>	17.3	15.3
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.5</b>	7.3	8.3
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.9</b>	14.0	14.0



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0104547 **Received** : 11 Jan 2024  
**Lab Number** : 06058703 **Diagnosed** : 12 Jan 2024  
**Unique Number** : 10830085 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 947 - WB Horicon HC**  
 N7296 County Rd V  
 Horicon, WI  
 US 53032  
 Contact: Tim Kieffer  
 tim.kieffer@gflenv.com  
 T: (608)219-0288  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)