



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
HITACHI 470LC HCMJAG60J00061713

Component
Right Swing Drive

Fluid
GEAR OIL SAE 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0192901	JR0155824	JR0161945
Sample Date		Client Info		04 Jan 2024	28 Jul 2023	02 May 2023
Machine Age	hrs	Client Info		6892	1474	6892
Oil Age	hrs	Client Info		6892	1474	500
Filter Age	hrs	Client Info		0	0	500
Oil Changed		Client Info		Changed	Not Chngd	Changed
Filter Changed		Client Info		Changed	N/A	Changed
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		29	20	35
Iron	ppm	ASTM D5185m	>400	66	51	76
Chromium	ppm	ASTM D5185m	>10	1	<1	2
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	<1	<1	0
Lead	ppm	ASTM D5185m	>50	0	0	0
Copper	ppm	ASTM D5185m	>200	1	<1	<1
Tin	ppm	ASTM D5185m	>10	<1	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>50	12	8	16
Potassium	ppm	ASTM D5185m	>20	0	0	2
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>170	1	1	0
Boron	ppm	ASTM D5185m	400	92	139	84
Barium	ppm	ASTM D5185m	200	2	0	0
Molybdenum	ppm	ASTM D5185m	12	0	0	1
Manganese	ppm	ASTM D5185m		2	1	2
Magnesium	ppm	ASTM D5185m	12	1	0	6
Calcium	ppm	ASTM D5185m	150	11	37	24
Phosphorus	ppm	ASTM D5185m	1650	660	685	496
Zinc	ppm	ASTM D5185m	125	5	3	7
Sulfur	ppm	ASTM D5185m	22500	16576	21830	15995
Visc @ 40°C	cSt	ASTM D445	143	154	152	187



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0192901 **Received** : 12 Jan 2024
Lab Number : 06059497 **Diagnosed** : 15 Jan 2024
Unique Number : 10830879 **Diagnostician** : Wes Davis
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

JRE - CHARLOTTE
 9550 STATESVILLE ROAD
 CHARLOTTE, NC
 US 28269
 Contact: CHARLOTTE SHOP
 myoung@jamesriverequipment.com
 T: (704)597-0211
 F: (704)596-6198