



# OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id  
**FREIGHTLINER 264**  
Component  
**Diesel Engine**  
Fluid  
**DIESEL ENGINE OIL SAE 15W40 (17 QTS)**

## RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>WC0870746</b>	WC0772970	WC0729730
Sample Date		Client Info		<b>20 Nov 2023</b>	17 Jan 2023	06 Sep 2022
Machine Age	mls	Client Info		<b>249266</b>	234192	229168
Oil Age	mls	Client Info		<b>0</b>	0	0
Filter Age	mls	Client Info		<b>0</b>	0	0
Oil Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Filter Changed		Client Info		<b>Not Changd</b>	Not Changd	Not Changd
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

## WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	<b>29</b>	44	21
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	2	1
Nickel	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m	>2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>14</b>	5	3
Lead	ppm	ASTM D5185m	>40	<b>0</b>	2	2
Copper	ppm	ASTM D5185m	>330	<b>2</b>	2	1
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	1
Vanadium	ppm	ASTM D5185m		<b>0</b>	<1	0
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

## CONTAMINATION











There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>9</b>	7	5
Potassium	ppm	ASTM D5185m	>20	<b>8</b>	4	1
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>6	<b>1.1</b>	1.6	1
Nitration	Abs/cm	*ASTM D7624	>20	<b>11.5</b>	12.2	10.2
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.5</b>	25.0	21.6
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

## FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	<b>5</b>	6	2
Boron	ppm	ASTM D5185m	250	<b>14</b>	14	22
Barium	ppm	ASTM D5185m	10	<b>4</b>	2	0
Molybdenum	ppm	ASTM D5185m	100	<b>95</b>	57	52
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m	450	<b>148</b>	119	94
Calcium	ppm	ASTM D5185m	3000	<b>2274</b>	2281	1952
Phosphorus	ppm	ASTM D5185m	1150	<b>1116</b>	983	884
Zinc	ppm	ASTM D5185m	1350	<b>1374</b>	1254	1095
Sulfur	ppm	ASTM D5185m	4250	<b>4049</b>	4200	3159
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.2</b>	17.5	14.6
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>6.5</b>	7.3	8.9
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.4</b>	14.9	14.8



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0870746 **Received** : 12 Jan 2024  
**Lab Number** : 06059760 **Diagnosed** : 15 Jan 2024  
**Unique Number** : 10831142 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**WAKE COUNTY PUBLIC SCHOOL SYSTEM**  
 1551 ROCK QUARRY ROAD  
 RALEIGH, NC  
 US 27610  
 Contact: DEVIN WEBER  
 dweber@wcpss.net  
 T: (919)856-8076  
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)