



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
FREIGHTLINER 722
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 15W40 (17 QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0870686	WC0806623	WC0729737
Sample Date		Client Info		07 Dec 2023	27 Apr 2023	16 Sep 2022
Machine Age	mls	Client Info		295232	249576	234215
Oil Age	mls	Client Info		0	0	0
Filter Age	mls	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	ABNORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>90	22	28	14
Chromium	ppm	ASTM D5185m	>20	<1	2	<1
Nickel	ppm	ASTM D5185m	>2	<1	<1	0
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	▲ 8	4
Lead	ppm	ASTM D5185m	>40	<1	0	<1
Copper	ppm	ASTM D5185m	>330	<1	1	<1
Tin	ppm	ASTM D5185m	>15	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	6	▲ 27	14
Potassium	ppm	ASTM D5185m	>20	25	4	4
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol	%	*ASTM D2982		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>6	1.2	0.5	0.4
Nitration	Abs/cm	*ASTM D7624	>20	9.1	10.0	9.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.6	19.8	21.5
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>158	15	3	2
Boron	ppm	ASTM D5185m	250	49	27	7
Barium	ppm	ASTM D5185m	10	3	2	0
Molybdenum	ppm	ASTM D5185m	100	73	83	64
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	450	135	148	363
Calcium	ppm	ASTM D5185m	3000	1767	2116	1793
Phosphorus	ppm	ASTM D5185m	1150	909	1043	1054
Zinc	ppm	ASTM D5185m	1350	1057	1246	1270
Sulfur	ppm	ASTM D5185m	4250	3508	3643	4207
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.4	16.5	17.6
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	7.7	6.9	8.7
Visc @ 100°C	cSt	ASTM D445	14.4	13.3	12.6	13.8



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0870686 **Received** : 12 Jan 2024
Lab Number : 06059812 **Diagnosed** : 16 Jan 2024
Unique Number : 10831194 **Diagnostician** : Don Baldrige
Test Package : MOB 1 (Additional Tests: Glycol, TBN)

WAKE COUNTY PUBLIC SCHOOL SYSTEM
 1551 ROCK QUARRY ROAD
 RALEIGH, NC
 US 27610
 Contact: DEVIN WEBER
 dweber@wcpss.net
 T: (919)856-8076
 F: x:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)