



TRAAP

Texas Refinery Advanced Analysis Program

OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id

T13

Component

2 Differential

Fluid

TRC MOLY ULTRA-TEC GEAR OIL 85W140 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		TR0001371	TR0001254	TR0000799
Sample Date		Client Info		09 Jan 2024	03 Oct 2023	10 Apr 2023
Machine Age	hrs	Client Info		5342	5045	4268
Oil Age	hrs	Client Info		5342	5045	4268
Filter Age	hrs	Client Info		0	5045	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	None	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>500	138	140	141
Chromium	ppm	ASTM D5185m	>10	2	2	<1
Nickel	ppm	ASTM D5185m	>10	0	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m		<1	0	0
Aluminum	ppm	ASTM D5185m	>25	5	6	3
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>100	0	2	0
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION












There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	58	59	50
Potassium	ppm	ASTM D5185m	>20	2	3	<1
Water		WC Method	>.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.2	NEG	NEG	NEG

FLUID CONDITION

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		4	4	4
Boron	ppm	ASTM D5185m		253	269	256
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	2	<1
Manganese	ppm	ASTM D5185m		6	6	6
Magnesium	ppm	ASTM D5185m		<1	1	4
Calcium	ppm	ASTM D5185m		21	23	21
Phosphorus	ppm	ASTM D5185m		1107	1051	998
Zinc	ppm	ASTM D5185m		5	11	0
Sulfur	ppm	ASTM D5185m		19771	23088	22472
Acid Number (AN)	mg KOH/g	ASTM D8045		1.32	1.51	1.40
Visc @ 40°C	cSt	ASTM D445		305	301	---
Visc @ 100°C	cSt	ASTM D445	30	26.1	26.2	26.2
Viscosity Index (VI)	Scale	ASTM D2270	105	111	113	---



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : TR0001371 **Received** : 12 Jan 2024
Lab Number : 06060373 **Diagnosed** : 16 Jan 2024
Unique Number : 10831755 **Diagnostician** : Don Baldrige
Test Package : MOB 2 (Additional Tests: KV100, VI)

To discuss this sample report, contact Customer Service at 1-800-827-0711.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

S S CONCRETE MATERIALS LLC
P.O. BOX 23283
BULLHEAD CITY, AZ
US 86439
Contact: SERVICE MANAGER
snsmaterials1@gmail.com
T:
F: (928)754-1991