



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>



Machine Id  
**427075-402234**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>GFL0098325</b>	GFL0098316	GFL0098286
Sample Date		Client Info		<b>05 Jan 2024</b>	15 Dec 2023	22 Nov 2023
Machine Age	hrs	Client Info		<b>39379</b>	39247	39065
Oil Age	hrs	Client Info		<b>700</b>	700	600
Filter Age	hrs	Client Info		<b>700</b>	700	0
Oil Changed		Client Info		<b>Changed</b>	Not Changd	Changed
Filter Changed		Client Info		<b>Changed</b>	Not Changed	Cleaned
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>120	<b>19</b>	8	26
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>5	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>20	<b>&lt;1</b>	1	<1
Lead	ppm	ASTM D5185m	>40	<b>&lt;1</b>	0	2
Copper	ppm	ASTM D5185m	>330	<b>2</b>	<1	3
Tin	ppm	ASTM D5185m	>15	<b>&lt;1</b>	<1	<1
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>25	<b>4</b>	2	2
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	1	0
Fuel		WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844	>4	<b>3.5</b>	1.8	3.9
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.4</b>	5.9	9.3
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>22.5</b>	20.0	25.7
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		<b>2</b>	<1	2
Boron	ppm	ASTM D5185m	0	<b>0</b>	1	<1
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	60	<b>56</b>	56	56
Manganese	ppm	ASTM D5185m	0	<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	1010	<b>913</b>	895	926
Calcium	ppm	ASTM D5185m	1070	<b>959</b>	972	1004
Phosphorus	ppm	ASTM D5185m	1150	<b>1008</b>	1037	999
Zinc	ppm	ASTM D5185m	1270	<b>1207</b>	1209	1210
Sulfur	ppm	ASTM D5185m	2060	<b>2905</b>	3030	2814
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>12.3</b>	12.7	15.1
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	<b>7.2</b>	8.9	5.7
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.7</b>	14.3	14.3



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0098325 **Received** : 16 Jan 2024  
**Lab Number** : 06060710 **Diagnosed** : 16 Jan 2024  
**Unique Number** : 10832092 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 822 - Springfield Hauling**  
 2120 West Bennett Street  
 Springfield, MO  
 US 65807  
 Contact: Dennis Moore  
 dennis.moore@gflenv.com  
 T: (417)403-3641  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)