



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Area
PCS - PORTABLE CRUSHING SERVICES
Machine Id
CASE SR240 SKID LD16 - PCS
Component
Diesel Engine
Fluid
CHEVRON DELO 400 SDE SAE 15W40 (--- QTS)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		KL0013959	KL0013073	KL0009672
Sample Date		Client Info		09 Jan 2024	03 Oct 2023	29 Jun 2023
Machine Age	hrs	Client Info		3691	2664	3691
Oil Age	hrs	Client Info		50	250	811
Filter Age	hrs	Client Info		50	250	811
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Filter Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>100	5	8	18
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>4	0	<1	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>20	5	1	5
Lead	ppm	ASTM D5185m	>40	0	1	<1
Copper	ppm	ASTM D5185m	>330	2	<1	1
Tin	ppm	ASTM D5185m	>15	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION











There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Silicon	ppm	ASTM D5185m	>25	8	14	16
Potassium	ppm	ASTM D5185m	>20	0	3	3
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
Soot %	%	*ASTM D7844	>3	0.1	0.1	0.1
Nitration	Abs/cm	*ASTM D7624	>20	7.3	5.8	4.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.4	18.5	20.1
Particles >4µm		ASTM D7647		1853	2619	4393
Particles >6µm		ASTM D7647	>5000	1009	1427	2393
Particles >14µm		ASTM D7647	>640	172	243	407
Particles >21µm		ASTM D7647	>160	58	82	137
Particles >38µm		ASTM D7647	>40	9	13	21
Particles >71µm		ASTM D7647	>10	1	1	2
Oil Cleanliness		ISO 4406 (c)	>19/16	17/15	18/15	18/16
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m		0	0	0
Boron	ppm	ASTM D5185m		121	258	439
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		84	94	93
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		87	244	369
Calcium	ppm	ASTM D5185m		2129	1801	1582
Phosphorus	ppm	ASTM D5185m	760	969	987	940
Zinc	ppm	ASTM D5185m	800	1137	1208	1083
Sulfur	ppm	ASTM D5185m	3000	4670	4977	5457
Oxidation	Abs/.1mm	*ASTM D7414	>25	14.9	13.4	15.0
Base Number (BN)	mg KOH/g	ASTM D2896	10	11.79	10.77	9.33
Visc @ 100°C	cSt	ASTM D445	14.6	13.7	13.6	13.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KL0013959 **Received** : 16 Jan 2024
Lab Number : 06061371 **Diagnosed** : 18 Jan 2024
Unique Number : 10832753 **Diagnostician** : Jonathan Hester
Test Package : MOB 2 (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

PIKES PEAK PERFORMANCE PRODUCTS

7888 BULLET RD
 PEYTON, CO
 US 80831

Contact: SCOTT RIGGS
 rriggs.pikespeakperformance@gmail.com

T: (303)434-0126

F: x: