



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
JOHN DEERE 700K LX2 (S/N 1T0700KXLJF334543)

Component
Right Final Drive

Fluid
JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0200891	JR0154777	JR0033731
Sample Date		Client Info		11 Jan 2024	31 Jan 2023	28 Mar 2022
Machine Age	hrs	Client Info		396	289	158
Oil Age	hrs	Client Info		396	289	158
Filter Age	hrs	Client Info		396	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Filter Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		43	31	31
Iron	ppm	ASTM D5185m	>500	80	75	73
Chromium	ppm	ASTM D5185m	>10	2	2	2
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>25	<1	<1	<1
Lead	ppm	ASTM D5185m	>25	0	<1	<1
Copper	ppm	ASTM D5185m	>50	2	<1	<1
Tin	ppm	ASTM D5185m	>10	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	MODER	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>75	34	36	36
Potassium	ppm	ASTM D5185m	>20	16	14	19
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		3	4	3
Boron	ppm	ASTM D5185m	6	0	0	4
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	1	1
Manganese	ppm	ASTM D5185m		4	4	4
Magnesium	ppm	ASTM D5185m	145	99	94	94
Calcium	ppm	ASTM D5185m	3570	3297	3382	3516
Phosphorus	ppm	ASTM D5185m	1290	1014	976	1059
Zinc	ppm	ASTM D5185m	1640	1264	1167	1267
Sulfur	ppm	ASTM D5185m		3462	4107	2779
Visc @ 40°C	cSt	ASTM D445	57.0	53.0	52.4	53.3



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0200891 **Received** : 16 Jan 2024
Lab Number : 06061420 **Diagnosed** : 17 Jan 2024
Unique Number : 10832802 **Diagnostician** : Wes Davis
Test Package : CONST (Additional Tests: PQ)

JRE - NEW BERN
 3816 MARTIN LUTHER KING BLVD
 NEW BERN, NC
 US 28562
 Contact: NEW BERN SHOP

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

nick.etheridge@jamesriverequipment.com; canastasio@wearcheckusa.com
 T:
 F: