



WEAR	<b>NORMAL</b>
CONTAMINATION	<b>NORMAL</b>
FLUID CONDITION	<b>NORMAL</b>

Machine Id  
**GENE NEAL**  
Component  
**Starboard Main Engine**  
Fluid  
**CHEVRON DELO 710 LE (250 GAL)**

**RECOMMENDATION**

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		<b>MW0057976</b>	MW0058002	MW0057999
Sample Date		Client Info		<b>01 Jan 2024</b>	05 Dec 2023	06 Nov 2023
Machine Age	hrs	Client Info		<b>27288</b>	26796	26359
Oil Age	hrs	Client Info		<b>1556</b>	1066	637
Filter Age	hrs	Client Info		<b>146</b>	1066	637
Oil Changed		Client Info		<b>N/A</b>	Not Changd	N/A
Filter Changed		Client Info		<b>N/A</b>	Not Changd	N/A
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

**WEAR**

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>75	<b>7</b>	8	7
Chromium	ppm	ASTM D5185m	>8	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>3	<b>0</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m	>15	<b>2</b>	2	2
Lead	ppm	ASTM D5185m	>18	<b>4</b>	3	2
Copper	ppm	ASTM D5185m	>80	<b>6</b>	6	5
Tin	ppm	ASTM D5185m	>14	<b>2</b>	3	2
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE

**CONTAMINATION**







There is no indication of any contamination in the oil.

Silicon	ppm	ASTM D5185m	>20	<b>4</b>	4	3
Potassium	ppm	ASTM D5185m	>20	<b>1</b>	<1	<1
Fuel		WC Method	>4.0	<b>&lt;1.0</b>	<1.0	<1.0
Water		WC Method	>0.1	<b>NEG</b>	NEG	NEG
Glycol		WC Method		<b>NEG</b>	NEG	NEG
Soot %	%	*ASTM D7844		<b>0.3</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.0</b>	7.2	6.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>15.4</b>	15.5	15.1
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	<b>NEG</b>	NEG	NEG

**FLUID CONDITION**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Sodium	ppm	ASTM D5185m	>75	<b>27</b>	18	6
Boron	ppm	ASTM D5185m		<b>44</b>	42	39
Barium	ppm	ASTM D5185m		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m		<b>46</b>	46	44
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m		<b>16</b>	18	14
Calcium	ppm	ASTM D5185m		<b>3465</b>	3520	3395
Phosphorus	ppm	ASTM D5185m		<b>12</b>	12	12
Zinc	ppm	ASTM D5185m	10	<b>10</b>	10	10
Sulfur	ppm	ASTM D5185m		<b>2291</b>	2261	2227
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>7.8</b>	7.9	7.5
Base Number (BN)	mg KOH/g	ASTM D2896	9.2	<b>6.8</b>	7.0	6.9
Visc @ 100°C	cSt	ASTM D445	15.5	<b>14.5</b>	14.6	14.8



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : MW0057976 **Received** : 16 Jan 2024  
**Lab Number** : 06061666 **Diagnosed** : 17 Jan 2024  
**Unique Number** : 10833048 **Diagnostician** : Wes Davis  
**Test Package** : MAR 2

**MAGNOLIA MARINE TRANSPORT**  
 697 HAINING ROAD  
 VICKSBURG, MS  
 US 39183

Contact: MMT MAINTENANCE PLANNERS  
 mmtmaintenanceplanners@ergon.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: x:  
 F: (601)638-8028