



OIL ANALYSIS REPORT

WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL

Machine Id
H/R JAW CRUSHER 5011 TANK

Component
Gearbox

Fluid
SHELL OMALA 220 (45 GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		WC0819300	WC0840632	WC0840619
Sample Date		Client Info		05 Dec 2023	03 Nov 2023	26 Sep 2023
Machine Age	hrs	Client Info		19786	19590	19351
Oil Age	hrs	Client Info		247	52	492
Filter Age	hrs	Client Info		247	52	492
Oil Changed		Client Info		N/A	Not Changd	Changed
Filter Changed		Client Info		Not Changed	Not Changed	Changed
Sample Status				NORMAL	NORMAL	SEVERE

WEAR

All component wear rates are normal.

Iron	ppm	ASTM D5185m	>200	53	13	425
Chromium	ppm	ASTM D5185m	>10	0	<1	3
Nickel	ppm	ASTM D5185m	>10	0	0	3
Titanium	ppm	ASTM D5185m		<1	<1	3
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	14	1	34
Lead	ppm	ASTM D5185m	>50	0	0	1
Copper	ppm	ASTM D5185m	>200	1	<1	3
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION










There is no indication of any contamination in the fluid.

Silicon	ppm	ASTM D5185m	>50	46	11	115
Potassium	ppm	ASTM D5185m	>20	1	2	10
Water		WC Method	>0.2	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	MODER
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG

FLUID CONDITION

The condition of the fluid is acceptable for the time in service.

Sodium	ppm	ASTM D5185m		2	0	12
Boron	ppm	ASTM D5185m	4.4	0	<1	4
Barium	ppm	ASTM D5185m	0.0	0	<1	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		1	0	6
Magnesium	ppm	ASTM D5185m	0	4	<1	7
Calcium	ppm	ASTM D5185m	0	10	2	22
Phosphorus	ppm	ASTM D5185m	215	303	302	342
Zinc	ppm	ASTM D5185m	0	4	0	0
Sulfur	ppm	ASTM D5185m	7039	10089	11894	12576
Visc @ 40°C	cSt	ASTM D445	220	189	184	211



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0819300 **Received** : 16 Jan 2024
Lab Number : 06062235 **Diagnosed** : 18 Jan 2024
Unique Number : 10833617 **Diagnostician** : Don Baldrige
Test Package : MOB 1

WAKE STONE CORPORATION-MONCURE
P.O. BOX 158
MONCURE, NC
US 27559
Contact: ROBBIE BOGAN
robbiebogan@wakestonecorp.com
T:
F: (919)776-1341

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)