



WEAR	NORMAL
CONTAMINATION	NORMAL
FLUID CONDITION	NORMAL



Machine Id
JOHN DEERE 844J DW844JX613105
Component
Front Differential
Fluid
JOHN DEERE GL-5 80W90 (--- GAL)

RECOMMENDATION

Resample at the next service interval to monitor.

Test	UOM	Method	Limit/Abn	Current	History1	History2
Sample Number		Client Info		JR0197879	JR0181217	JR0186464
Sample Date		Client Info		16 Jan 2024	16 Oct 2023	08 Sep 2023
Machine Age	hrs	Client Info		34513	34151	34151
Oil Age	hrs	Client Info		362	2	527
Filter Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Changed	Not Changd
Filter Changed		Client Info		N/A	N/A	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL

WEAR

All component wear rates are normal.

PQ		ASTM D8184		310	31	14
Iron	ppm	ASTM D5185m	>1501	426	50	2
Chromium	ppm	ASTM D5185m	>11	4	<1	0
Nickel	ppm	ASTM D5185m	>10	4	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>21	3	<1	<1
Lead	ppm	ASTM D5185m	>51	0	0	<1
Copper	ppm	ASTM D5185m	>101	11	1	0
Tin	ppm	ASTM D5185m	>10	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE

CONTAMINATION

There is no indication of any contamination in the oil.


Silicon	ppm	ASTM D5185m	>31	12	5	1
Potassium	ppm	ASTM D5185m	>20	<1	<1	1
Water		WC Method	>0.1	NEG	NEG	NEG
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG

FLUID CONDITION


The condition of the oil is acceptable for the time in service.

Sodium	ppm	ASTM D5185m	>51	6	2	0
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		6	<1	0
Magnesium	ppm	ASTM D5185m		6	0	0
Calcium	ppm	ASTM D5185m		194	201	1
Phosphorus	ppm	ASTM D5185m		2147	2197	320
Zinc	ppm	ASTM D5185m		80	48	0
Sulfur	ppm	ASTM D5185m		24587	24889	21690
Visc @ 40°C	cSt	ASTM D445		146	150	143


Viscosity @ 40°C




PQ




Ferrous Alloys




Non-ferrous Metals



PQ



Viscosity @ 40°C



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0197879 **Received** : 17 Jan 2024
Lab Number : 06063099 **Diagnosed** : 18 Jan 2024
Unique Number : 10834481 **Diagnostician** : Sean Felton
Test Package : CONST (Additional Tests: PQ)

FUQUAY - MARTIN MARIETTA
 7400 BUCKHORN DUNCAN RD
 HOLLY SPRINGS, NC
 US 27549
 Contact: DARIN HESS
 darin.hess@martinmarietta.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: